000-972^{Q&As}

ILE RPG Programmer

Pass IBM 000-972 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4lead.com/000-972.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

Which of the following determine the activation group in which an ILE RPG program will run?

A. The value of the ACTGRP parameter in the job description.

B. The activation group in which the calling job was running.

C. The value of the ACTGRP parameter when the program was created.

D. The value specified in a binding directory when the program was created.

Correct Answer: C

QUESTION 2

Given the following code sample:

D amount s 3 0 inz(900)

/free

monitor;

amount += 100;

on-error *program;

amount = *hival;

on-error *all;

amount = *hival;

monitor;

amount -= 100;

on-error *program;

amount = 0;

on-error *all;

amount = 100;

endmon;

endmon;

What is the value of AMOUNT upon completion?

A. 0

B. 999

C. 100

D. 899

Correct Answer: B

QUESTION 3

Given the following code sample:

D DecData Ds Qualified D Num1 7p 2 D Num2 7p 2 D Num3 7p 2 D CharData Ds Qualified D Num1 9a D Num2 9a D Num3 9a /Free Eval-Corr CharData = DecData;

Which of the following statements is true?

A. The program will run but no fields will be copied.

B. The program will run and all fields will be copied.

C. The program will not compile because the DS fields are not compatible.

D. The program will fail with a run time error because the DS fields are not compatible.

Correct Answer: A

QUESTION 4

Given the following code sample:

DName+++++++++++ETDsFrom+++To/L+++IDc.Keywords++++++++++++++++++

D x s 5i 0 inz(0) D count s 5i 0 inz(0) /free for x = 2 to 3 by 2; count += x;

endfor;

What are the values of x and count after the loop completes?

A. x = 3 count = 5

B. x = 4 count = 6

C. x = 4 count = 2

D. x = 2 count = 2

Correct Answer: C

QUESTION 5

Which of the following "D" specifications defines a valid array with all elements initialized to values of 100?

A. DName+++++++++++ETDsFrom+++To/L+++IDc.Keywords++++++++++++ D POS S 3 DIM(15) INZ(100)

B. DName+++++++++++ETDsFrom+++To/L+++IDc.Keywords++++++++++++ D POS S 3 0 DIM(15) INZ(100)

C. DName+++++++++++ETDsFrom+++To/L+++IDc.Keywords++++++++++++ D POS S 3P 0 DIM(15) VALUE(100)

D. DName+++++++++++ETDsFrom+++To/L+++IDc.Keywords++++++++++++ D POS S 3S 0 DIM(15) INZ(100 : *ALL)

Correct Answer: B

000-972 PDF Dumps   000-972 VCE Dumps   000-972 Exam Questions

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.pass4lead.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: