![Pass2Lead logo](https://Pass2Lead.com)
117-201^{Q&As}

Linux Advanced Administration

Pass Lpi 117-201 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass2lead.com/117-201.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Lpi Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

![Pass2Lead logo](https://Pass2Lead.com)
QUESTION 1

You wish to notify all users that you have to take down a service on which they rely. What command will allow you to send a message to all currently logged on users? Enter only the command, not the path.

Correct Answer: wall

QUESTION 2

Which TWO statements about crontab are true?

A. Every user may have their own crontab.

B. Changing a crontab requires a reload/restart of the cron deamon.

C. The cron daemon reloads crontab files automatically when necessary.

D. hourly is the same as "0 * * * *".

E. A cron daemon must run for each existing crontab.

Correct Answer: AD

QUESTION 3

Running tcpdump -nli ethl \\'icmp\\' shows the following output:

11:56:35.599063 IP 192.168.123.5 > 194.25.2.129: icmp 64: echo request seq 1

11:56:35.670910 IP 194.25.2.129 > 192.168.123.5: icmp 64: echo reply seq 1

What command was used on the host 192.168.123.5, to generate this output?

Correct Answer: ping

QUESTION 4

A system is running out of swap space. To initialise 5GB of additional swap space, which combination of commands should be used?

A. dd if=/dev/zero of=/tmp/swapfile bs=1024 count=5120000; mkswap /tmp/swapfile; swapon /tmp/ swapfile

B. dd if=/dev/zero of=/tmp/swapfile bs=1024 count=5120000; swap on /tmp/swapfile

C. dd if=/dev/zero of=/tmp/swapfile bs=1024 count=5120000; mkswap /tmp/swapfile; mount /tmp/swapfile

D. touch -5G /tmp/swapfile; swapon /tmp/swapfile

E. mkswap /tmp/swapfile 512000; swapon /tmp/swapfile

Correct Answer: A

QUESTION 5

What command is used to permanently set the options in the kernel when making a boot disk?

A. blockdev

B. kconfig

C. lilo

D. rdev

E. dd

Correct Answer: D

117-201 PDF Dumps   **117-201 VCE Dumps**   **117-201 Study Guide**