

# 156-315.80<sup>Q&As</sup>

Check Point Certified Security Expert (CCSE) R80

## Pass CheckPoint 156-315.80 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/156-315-80.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by CheckPoint Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

How would you deploy TE250X Check Point appliance just for email traffic and in-line mode without a Check Point Security Gateway?

- A. Install appliance TE250X on SpanPort on LAN switch in MTA mode.
- B. Install appliance TE250X in standalone mode and setup MTA.
- C. You can utilize only Check Point Cloud Services for this scenario.
- D. It is not possible, always Check Point SGW is needed to forward emails to SandBlast appliance.

Correct Answer: C

---

**QUESTION 2**

What is the valid range for Virtual Router Identifier (VRID) value in a Virtual Routing Redundancy Protocol (VRRP) configuration?

- A. 1-254
- B. 1-255
- C. 0-254
- D. 0 ?255

Correct Answer: B

---

**QUESTION 3**

Which command is used to set the CCP protocol to Multicast?

- A. cphaprob set\_ccp multicast
- B. cphaconf set\_ccp multicast
- C. cphaconf set\_ccp no\_broadcast
- D. cphaprob set\_ccp no\_broadcast

Correct Answer: B

Reference: [https://supportcenter.checkpoint.com/supportcenter/portal?eventSubmit\\_doGoviewsolutiondetails=&andsolutionid=sk20576](https://supportcenter.checkpoint.com/supportcenter/portal?eventSubmit_doGoviewsolutiondetails=&andsolutionid=sk20576)

---

**QUESTION 4**

What is the order of NAT priorities?

- A. Static NAT, IP pool NAT, hide NAT
- B. IP pool NAT, static NAT, hide NAT
- C. Static NAT, automatic NAT, hide NAT
- D. Static NAT, hide NAT, IP pool NAT

Correct Answer: A

Reference: [https://sc1.checkpoint.com/documents/R77/CP\\_R77\\_Firewall\\_WebAdmin/6724.htm#o6919](https://sc1.checkpoint.com/documents/R77/CP_R77_Firewall_WebAdmin/6724.htm#o6919)

---

#### QUESTION 5

What needs to be configured if the NAT property `Translate destination or client side` is not enabled in Global Properties?

- A. A host route to route to the destination IP.
- B. Use the file local.arp to add the ARP entries for NAT to work.
- C. Nothing, the Gateway takes care of all details necessary.
- D. Enabling `Allow bi-directional NAT` for NAT to work correctly.

Correct Answer: C

[Latest 156-315.80 Dumps](#)

[156-315.80 PDF Dumps](#)

[156-315.80 Study Guide](#)