

156-915.80^{Q&As}

Check Point Certified Security Expert Update - R80.10

Pass CheckPoint 156-915.80 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/156-915-80.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CheckPoint Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

When configuring SmartEvent Initial settings, you must specify a basic topology for SmartEvent to help it calculate traffic direction for events. What is this setting called, and what are you defining?

- A. Network; and defining your Class A space
- B. Topology; and you are defining the Internal network
- C. Internal addresses; you are defining the gateways
- D. Internal network(s); you are defining your networks

Correct Answer: B

QUESTION 2

When restoring R80 using the command `upgrade_import`, which of the following items are NOT restored?

- A. SIC Certificates
- B. Licenses
- C. Route tables
- D. Global properties

Correct Answer: C

QUESTION 3

Which features are only supported with R80.10 Gateways but not R77.x?

- A. Access Control policy unifies the Firewall, Application Control and URL Filtering, Data Awareness, and Mobile Access Software Blade policies.
- B. Limits the upload and download throughput for streaming media in the company to 1 Gbps.
- C. The rule base can be built of layers, each containing a set of the security rules. Layers are inspected in the order in which they are defined, allowing control over the rule base flow and which security functionalities take precedence.
- D. Time object to a rule to make the rule active only during specified times.

Correct Answer: C

Reference: <http://slideplayer.com/slide/12183998/>

QUESTION 4

You have a diskless appliance platform. How do you keep swap file wear to a minimum?

- A. Issue FW-1 bases its package structure on the Security Management Server, dynamically loading when the firewall is booted.
- B. The external PCMCIA-based flash extension has the swap file mapped to it, allowing easy replacement.
- C. Use PRAM flash devices, eliminating the longevity.
- D. A RAM drive reduces the swap file thrashing which causes fast wear on the device.

Correct Answer: D

QUESTION 5

John detected high load on sync interface. Which is most recommended solution?

- A. For short connections like http service ?delay sync for 2 seconds
- B. Add a second interface to handle sync traffic
- C. For short connections like http service ?do not sync
- D. For short connections like icmp service ?delay sync for 2 seconds

Correct Answer: A

[Latest 156-915.80 Dumps](#)

[156-915.80 VCE Dumps](#)

[156-915.80 Braindumps](#)