

# 1Y0-A21<sup>Q&As</sup>

Basic Administration for Citrix NetScaler 9.2

## Pass Citrix 1Y0-A21 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/1y0-a21.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



### QUESTION 1

An administrator needs to configure a monitor to track the health of an IMAP service configured on a NetScaler system.

Which type of monitor must the administrator configure to track the health of this entity?

- A. Load
- B. User
- C. Inline
- D. Server Application State Protocol (SASP)

Correct Answer: B

---

### QUESTION 2

An organization has a NetScaler HA pair that needs to be upgraded to the most recent build available for NetScaler version 9.2.

According to best practices, which three steps should the NetScaler administrator take to minimize downtime while accomplishing this task? (Choose three.)

- A. Disable propagation for the HA pair.
- B. Disable synchronization for the HA pair.
- C. Migrate the configuration to version 9.2.
- D. Disable heartbeat communication (HAMON).
- E. Enable Independent Network Configuration (INC).
- F. Upgrade the Secondary NetScaler unit in the HA pair first.

Correct Answer: ABF

---

### QUESTION 3

Scenario: An administrator is managing a network environment with a stand-alone NetScaler system. The speed of the interfaces currently being used is inadequate for the amount of traffic that the NetScaler system is managing. The administrator needs to increase the available bandwidth on the system. The administrator also wants to add redundancy to the interfaces for failover.

What can the administrator do to meet the needs of this scenario with minimal change to the current network environment?

- A. Configure multiplexing.

- B. Configure link aggregation.
- C. Create a load balancing policy for the interfaces.
- D. Add a second NetScaler device and configure HA.

Correct Answer: B

---

#### QUESTION 4

Scenario: An administrator has created a policy expression to identify URLs with the .JSP suffix. The administrator plans to use the policy expression to prevent URLs with the .JSP suffix from being compressed when the HTTP response is received.

How can the administrator associate the policy expression and action to achieve the desired result?

- A. Configure the action, then add a compression policy with the policy expression.
- B. Add a filter with the policy expression and the action specified, then bind the policy.
- C. Configure the action, then add the filter with the policy expression and the action specified.
- D. Add a compression policy with the policy expression and action specified, then bind the policy.

Correct Answer: D

---

#### QUESTION 5

Which three components does an administrator have to configure in order to establish a basic content switching setup? (Choose three.)

- A. GSLB sites
- B. SSL Offload
- C. ADNS services
- D. Rule or URL-based policies
- E. Load balancing virtual server
- F. Content switching virtual server

Correct Answer: DEF

[Latest 1Y0-A21 Dumps](#)

[1Y0-A21 PDF Dumps](#)

[1Y0-A21 Exam Questions](#)