



1Z0-804^{Q&As}

Java SE 7 Programmer II

Pass Oracle 1Z0-804 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4lead.com/1Z0-804.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Given the following code fragment:

```
public static void main(String[] args) {  
  
    Connection conn = null;  
  
    Deque myDeque = new ArrayDeque();  
  
    myDeque.add("one");  
  
    myDeque.add("two");  
  
    myDeque.add("three");  
  
    System.out.println(myDeque.remove());  
  
}
```

What is the result?

- A. Three
- B. One
- C. Compilation fails
- D. The program runs, but prints no output

Correct Answer: B

The `ArrayDeque.remove()` method retrieves and removes the head of the queue represented by this deque. The head of the queue is item "one". Reference: `java.util Class ArrayDeque`

QUESTION 2

Given the code fragment:

```
try {  
  
    String query = "SELECT * FROM Employee WHERE ID=110";  
  
    Statement stmt = conn.createStatement();  
  
    ResultSet rs = stmt.executeQuery(query);  
  
    System.out.println("Employee ID: " + rs.getInt("ID"));  
  
} catch (Exception se) {  
  
    System.out.println("Error");  
  
}
```



```
}
```

Assume that the SQL query matches one record. What is the result of compiling and executing this code?

- A. The code prints Error.
- B. The code prints the employee ID.
- C. Compilation fails due to an error at line 13.
- D. Compilation fails due to an error at line 14.

Correct Answer: B

The code compiles fine. The code will run fine.

`public int getInt(String columnName)` throws `SQLException` Retrieves the value of the designated column in the current row of this `ResultSet` object as an `int` in the Java programming language

QUESTION 3

Given the code fragment:

```
String query = "SELECT ID FROM Employee";  
try (Statement stmt = conn.createStatement()) {  
    ResultSet rs = stmt.executeQuery(query);  
    stmt.executeQuery("SELECT ID FROM Customer"); // Line ***  
    while (rs.next()) {  
        // process the results  
        System.out.println ("Employee ID: " + rs.getInt("ID"));  
    }  
} catch (Exception e) {  
    System.err.println ("Error");  
}
```

Assume that the SQL queries return records.

What is the result of compiling and executing this code fragment?

- A. The program prints employee IDs
- B. The program prints customer IDs
- C. The program prints Error



D. Compilation fails on line ***

Correct Answer: A

The program compiles and runs fine. Both executeQuery statements will run.

The first executeQuery statement (ResultSet rs = stmt.executeQuery(query);) will set the rs ResultSet. It will be used in the while loop. EmployIDs will be printed.

Note: Executes the given SQL statement, which returns a single ResultSet object.

Parameters:

sql - an SQL statement to be sent to the database, typically a static SQL SELECT statement

Returns:

a ResultSet object that contains the data produced by the given query; never null

QUESTION 4

Given:

```
import java.util.ArrayList;
import java.util.Collections;
import java.util.List;

public class NameList {
    public static void main(String[] args) {
        List<String> nameList = new ArrayList<>(3);

        nameList.add("John Adams");
        nameList.add("George Washington");
        nameList.add("Thomas Jefferson");

        Collections.sort(nameList);
        for (String name : nameList) {
            System.out.println(name);
        }
    }
}
```

What is the result?

- A. John Adams George Washington Thomas Jefferson
- B. George Washington John Adams Thomas Jefferson
- C. Thomas Jefferson John Adams George Washington
- D. An exception is thrown at runtime
- E. Compilation fails



Correct Answer: B

The program compiles and runs fine.

At runtime the NameList is built and then sorted.

QUESTION 5

Which two codes correctly represent a standard language locale code?

- A. ES
- B. FR
- C. U8
- D. Es
- E. fr
- F. u8

Correct Answer: AD

Language codes are defined by ISO 639, an international standard that assigns two- and three-letter codes to most languages of the world.

Locale uses the two-letter codes to identify the target language.

ES, Es: Spanish

Reference: ISO 639

[1Z0-804 PDF Dumps](#)

[1Z0-804 Practice Test](#)

[1Z0-804 Study Guide](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.pass4lead.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4lead, All Rights Reserved.