Pass2Lead

https://Pass2Lead.com

1Z0-822^{Q&As}

Oracle Solaris 11 Advanced System Administration

Pass Oracle 1Z0-822 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass2lead.com/1z0-822.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle
Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

Consider the following:


```
root@Sol11-desktop:~# pkg publisher solaris

Publisher: solaris
Alias:
Origin URI: https://pkg.oracle.com/solaris/support/
SSL Key: /var/pkg/ssl/7943aaec54a3298eb1206d2ad3929eff6d865c4a
SSL Cert: /var/pkg/ssl/54936e6c939d2f9f16789d54d9a8558671eb6fd5
Cert. Effective Date: Wed Jun 22 15:16:45 2011
Cert. Expiration Date: Fri Jun 29 15:16:45 2012
Client UUID: 00000000-3f24-fe2c-0000-000068120608
Catalog Updated: Thu Feb 09 04:49:05 2012
Enabled: Yes
Signature Policy: verify
```

What is true concerning this publisher\\'s Signature Policy?

A. Only packages from this publisher must have at least one valid signature.

B. All manifests from this publisher must have a cryptographic signature.

C. All newly installed packages must have at least one valid signature.

D. Signed and unsigned packages from this publisher can be installed.

Correct Answer: D

QUESTION 2

What can you retrieve using a vmstat command?

A. the number of kernel threads active on the system

B. the amount of physical memory available on the system

C. the rate of system calls made on the system

D. the amount of time spent on paging activity

Correct Answer: A

QUESTION 3

You have set resource controls on a project. Now you want to set up syslog to monitor a particular resource control and log a message whenever the resource control is exceeded. Which option would you choose to activate logging on the global resource control facility to establish a syslog action on a resource control?

A. Use the rctladm command to enable the global syslog attribute of a resource control.

![Pass2Lead](https://Pass2Lead.com)
B. Use the prctl command to enable the global syslog attribute of resource control.

C. Use the ipcs command to enable the global syslog attribute of a resource control.

D. Use the setrctl command to enable the global syslog attribute of a resource control.

E. By default, global logging of resource control violations is already enabled. Make an entry in the syslog.conf file and refresh the system-log service.

Correct Answer: A

QUESTION 4

You administer an Oracle Solaris 11 system that uses a user-defined Network Configuration Profile (NCP). You now need to modify the DNS name servers. Select the profile type that you will need to modify.

A. Automatic-NCP

B. Location profile

C. Network Configuration Unit

D. External Network Modifiers

Correct Answer: A

QUESTION 5

What are targets for IPMP probe-based failure detection configured by?

A. responses to SNMP requests

B. specifying host routes in the routing table

C. specifying hosts in /etc/default/mpathd

D. setting the property svc:/network/ipmp/config/transitive-probing

Correct Answer: B

[Latest 1Z0-822 Dumps](https://www.pass2lead.com/1z0-822.html)   [1Z0-822 Practice Test](https://www.pass2lead.com/1z0-822.html)   [1Z0-822 Braindumps](https://www.pass2lead.com/1z0-822.html)