

# 1Y0-230<sup>Q&As</sup>

Citrix NetScaler 12 Essentials and Unified Gateway

## Pass Citrix 1Y0-230 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/1y0-230.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



### QUESTION 1

Which Citrix ADC hardware or software platform offers a Multi-Tenant solution?

- A. VPX
- B. CPX
- C. MPX
- D. SDX

Correct Answer: D

Reference: [https://www.citrix.com/content/dam/citrix/en\\_us/documents/products-solutions/maximizingmulti-tenancy-with-citrix-netscaler-en.pdf](https://www.citrix.com/content/dam/citrix/en_us/documents/products-solutions/maximizingmulti-tenancy-with-citrix-netscaler-en.pdf)

---

### QUESTION 2

Where should a Citrix Administrator configure SmartControl restrictions?

- A. Citrix Gateway
- B. XenDesktop Delivery Controller
- C. Citrix Gateway, Citrix Delivery Controller and StoreFront
- D. StoreFront and Citrix Delivery Controller

Correct Answer: A

Reference: <https://docs.citrix.com/en-us/netscaler-gateway/12/integrate-web-interface-apps/smartcontrol.html>

---

### QUESTION 3

Scenario: A NetScaler is configured with the following modes:

-MAC-based Forwarding -USIP -USNIP -Layer 3 mode

A Citrix Administrator configured a new router and now requires some of the incoming and outgoing traffic to take different paths through the new router. However, the administrator notices that this is failing and takes a network trace. After a short monitoring period, the administrator notices that the packets are still NOT getting to the new router from the NetScaler.

Which mode should the administrator disable on the NetScaler to facilitate the addition of the new router and successfully route the packets?

- A. MAC-based Forwarding
- B. USIP

C. Layer 3 mode

D. USNIP

Correct Answer: D

---

#### QUESTION 4

Scenario: A Citrix Administrator is configuring balancing on a NetScaler appliance for the company web servers. The administrator needs to create a custom monitor that will look for a specific keyword response from the website and will be used to keep the services in an UP state.

Which type of monitor can the administrator create to accomplish this scenario?

A. An HTTP-ECV monitor with the keyword in the Special Parameters- Receive String field.

B. A customer TCP-ECV monitor with the keyword in the Special Parameters- Receive String field.

C. An HTTP monitor with the keyword in the Special Parameters- Response Codes field.

D. A TCP monitor with the keyword in the Special Parameters- Response Codes field.

Correct Answer: C

---

#### QUESTION 5

In an environment which requires secure user access, a Citrix Administrator configures Authentication, Authorization and Auditing (AAA) to redirect a user to the logon page.

Which four steps are required to complete the authentication process? (Choose four.)

A. Configure a syslog server to capture invalid logon attempts?

B. Verify that the user is authorized to access specific intranet content

C. Collect the user's credentials to cache them in a directory that is accessible through LDAP

D. Log the user accesses, including invalid login attempts, in an audit log

E. Create a load-balancing virtual server to redirect for secure access

F. Maintain a session timeout, after which users must authenticate again to regain access to the intranet

G. Apply specified two-factor authentication method

Correct Answer: CEFG

---