

# 1Y0-231<sup>Q&As</sup>

Deploy and Manage Citrix ADC 13 with Citrix Gateway

## Pass Citrix 1Y0-231 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/1y0-231.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



### QUESTION 1

Scenario: A Citrix Administrator configured Citrix ADC load balancing to send requests to one of three identical backend servers. Each server handles multiple protocols, and load balancing is set up in round-robin mode. The current load-balancing setup on the Citrix ADC is:

One load-balancing virtual server with one externally accessible VIP  
One service created for each protocol type  
One server entity for each backend resource

During business hours, the administrator wants to make changes to one backend server without affecting the other servers

What is the most efficient way for the administrator to ensure that all traffic is routed away from the server without impeding responses from other resources?

- A. Disable the backend server entity targeted for change.
- B. Disable the load-balancing virtual server.
- C. Disable the backend service entity targeted for change.
- D. Unbind the correct server entity from the load-balancing virtual server.

Correct Answer: D

---

### QUESTION 2

Which Citrix ADC platform offers an out-of-the-box, hardware-independent, multi-tenant solution?

- A. SDX
- B. CPX
- C. MPX
- D. VPX

Correct Answer: A

Reference: [https://www.citrix.com/content/dam/citrix/en\\_us/documents/data-sheet/citrix-adc-hardwareplatforms.pdf](https://www.citrix.com/content/dam/citrix/en_us/documents/data-sheet/citrix-adc-hardwareplatforms.pdf)

---

### QUESTION 3

A Citrix Administrator needs to configure a Citrix ADC high availability (HA) pair with each Citrix ADC in a different subnet.

What does the administrator need to do for HA to work in different subnets?

- A. Configure SyncVLAN

- B. Turn on Independent Network Configuration (INC) mode
- C. Turn on HA monitoring on all Interfaces
- D. Turn on fail-safe mode

Correct Answer: B

---

#### QUESTION 4

If a user device does NOT comply with a company's security requirements, which type of policy can a Citrix Administrator apply to a Citrix Gateway virtual server to limit access to Citrix Virtual Apps and Desktops resources?

- A. Session
- B. Responder
- C. Authorization
- D. Traffic

Correct Answer: A

Reference: [https://www.citrix.com/content/dam/citrix/en\\_us/documents/products-solutions/creating-andenforcing-advanced-access-policies-with-xenapp.pdf](https://www.citrix.com/content/dam/citrix/en_us/documents/products-solutions/creating-andenforcing-advanced-access-policies-with-xenapp.pdf)

---

#### QUESTION 5

In a single-hop deployment, a Citrix Administrator needs to use a client's IP address as the source IP address for Citrix ADC-to-server connections.

Which Citrix ADC mode can the administrator use to meet this requirement?

- A. USIP
- B. USNIP
- C. Layer 2
- D. Layer 3

Correct Answer: A

Reference: <https://docs.citrix.com/en-us/citrix-adc/current-release/load-balancing/load-balancingadvanced-settings/usip-of-client.html>