

1Y0-253^{Q&As}

Implementing Citrix NetScaler 10.5 for App and Desktop Solutions

Pass Citrix 1Y0-253 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/1y0-253.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Scenario: A new software package has been developed at an organization. The organization has hired Field Sales Engineers to accompany Sales Executives when demonstrating the new software package. The demonstration software is hosted on an internal web server. A Citrix Administrator needs to configure the NetScaler to ensure end-to-end connectivity. Which feature on the NetScaler must the administrator ensure is enabled to provide secure access from the public network?

- A. Sure Connect
- B. SSL Offloading
- C. Application Firewall
- D. Global Server Load Balancing

Correct Answer: B

QUESTION 2

Which action could an administrator take to configure auditing of logon events for all the employees who connected through the NetScaler Gateway for the current day?

- A. Run `ldf -hl` from the NetScaler command-line interface.
- B. Configure a Syslog policy to send events to a remote server.
- C. Run `lcat aaa.debugl` from the NetScaler command-line interface.
- D. Review logon events through Reporting > Access Gateway > AAA > AAA Sessions.

Correct Answer: B

QUESTION 3

Which two steps must a Citrix Administrator take to allow additional users to access resources using the NetScaler Gateway Plug-in after the administrator installs the universal license on the NetScaler Gateway? (Choose two.)

- A. Set ICA Proxy to OFF.
- B. Configure Citrix Receiver Home Page.
- C. Change the authentication AAA settings.
- D. Set Single Sign-on with Windows to OFF.

Correct Answer: AC

QUESTION 4

Which IP address must be unique on each node in a high availability configuration?

- A. virtual IP (vIP)
- B. Mapped IP (MIP)
- C. Subnet IP (SNIP)
- D. NetScaler IP (NSIP)

Correct Answer: B

QUESTION 5

Which two actions should an administrator take to ensure the first NetScaler node configured in a high availability (HA) pair remains the primary node after a second node is added? (Choose two.)

- A. Set Stay Primary on the first node.
- B. Configure Stay Secondary on the second node.
- C. Enable HA Sync before adding the second node.
- D. Create a Route Monitor to ensure proper synchronization.
- E. Ensure that INC mode is enabled during creation of the HA pair.

Correct Answer: AB

[1Y0-253 PDF Dumps](#)

[1Y0-253 Exam Questions](#)

[1Y0-253 Braindumps](#)