

1Y0-351^{Q&As}

Citrix NetScaler 10.5 Essentials and Networking





Pass Citrix 1Y0-351 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/1y0-351.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Scenario: A network engineer would like to prevent blacklisted remote clients from accessing NetScaler hosted application services. An IP address blacklist database is maintained by an external company and available to query over the Internet.

The engineer would like to reject any connections from IP addresses that are contained in the blacklist.

What could the engineer configure to achieve this goal?

- A. SSL offload
- B. HTTP callout
- C. URL transformation
- D. SSL certification revocation list check

Correct Answer: B

QUESTION 2

Which command will allow an engineer to change the NetScaler IP (NSIP) from the command-line interface?

- A. `add ns ip 10.100.10.100 255.255.255.0 -type SNIP`
- B. `add ns ip 10.100.10.100 255.255.255.0 -type NSIP`
- C. `set ns config -ipaddress 10.100.10.100 -netmask 255.255.255.0`
- D. `set ns ip 10.100.10.100 -netmask 255.255.255.0 -mgmtaccess enabled`

Correct Answer: C

QUESTION 3

Scenario: A NetScaler Engineer is troubleshooting a high-availability issue. The engineer needs to determine if the port being used by the high-availability heartbeats is blocked.

Which port is used by high-availability heartbeats?

- A.
- B.
- C.
- D.

Correct Answer: A

QUESTION 4

QUESTION NO: 118

Which two options could a NetScaler Engineer configure to ensure that a revoked client certificate CANNOT be used for a client certificate authentication? (Choose two.)

- A. Server Name Indication (SNI)
- B. Certificate Revocation List (CRL)
- C. Certificate Signing Request (CSR)
- D. Online Certification Status Protocol (OCSP)

Correct Answer: BD

QUESTION 5

How could an engineer configure a monitor to ensure that a server is marked as DOWN if the monitor test is successful?

- A. Enable the LRTM option for the monitor
- B. Enable the Reverse option for the monitor
- C. Disable Down state flush for the service group
- D. Disable the Health monitoring option for the service group

Correct Answer: B

[Latest 1Y0-351 Dumps](#)

[1Y0-351 PDF Dumps](#)

[1Y0-351 Braindumps](#)