

1Z0-1033-20^{Q&As}

Oracle CPQ Cloud Service 2020 Implementation Essentials

Pass Oracle 1Z0-1033-20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/1z0-1033-20.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A multi-select attribute with five options is displayed as check boxes. Depending on the conditions, the Configurator should show a user three of these five options.

How do you accomplish this?

- A. by writing a Constraint rule
- B. by writing a Hiding rule
- C. by writing a Recommendation rule
- D. by writing a Pricing rule

Correct Answer: B

QUESTION 2

What is the correct order of execution of Configuration rules for an attribute that has both Recommendation and Constraint rules written on it?

- A. Recommendation, Constraint, Hiding, Recommended Item
- B. Constraint, Hiding, Recommendation, Recommended Item
- C. Constraint, Recommendation, Constraint, Hiding, Recommended Item
- D. Hiding, Constraint, Recommendation, Recommended Item
- E. Recommendation, Recommended Item, Hiding, Constraint

Correct Answer: D

QUESTION 3

Which two statements are false about BML? (Choose two.)

- A. BML follows the Object-Oriented programming model.
- B. BML does not need to be externally compiled as the application compiles the BML.
- C. BML has characteristics of Compiled and Interpretive programming.
- D. BML is a C++ based markup language.

Correct Answer: BD

QUESTION 4

Given the following code:

```
xmlPayload = "<?xml version= \"1.0\" encoding= \"UTF-8\"?><library><book lang= \"en\">Spring in  
Action</book><book lang= \"fr\">J2EE Blueprint</book></library>\";  
xpath = string [1];  
xpath [0] = \"/library/book/@lang\";  
output = rwxmlmultiple (xmlPayload, xpath);  
  
for xpath in xpath {  
    print (\" (key) = ( \" + xpath + \" )\");  
    values = string [1];  
    values = get (output, xpath);  
  
    for value in values {  
        print (\" (value) = (\" + value + \" )\");  
    }  
}  
return \" \";
```

What will be returned?

- A. (key) = (/library/book/@lang)(value) = (en)(value) = (fr)
- B. (key) = (/lang/book/library)(value) = (en)(value) = (fr)
- C. (key) = (/library/book/@lang)(value) = (English)(value) = (French)
- D. (key) = (/library/book/@lang)(value) = (Spring in Action)(value) = (J2EE Blueprint)

Correct Answer: B

QUESTION 5

Given the following code:

```
myArray = float [] {154.68, 174.29, 957.03, 947.56, 759.37};  
result = _____ (myArray, 174.29);  
return result;
```

Which function, when filled in the blank, will return a value of 1?

- A. findinarray
- B. arrayfind
- C. findarray
- D. findinsidearray

Correct Answer: C

[Latest 1Z0-1033-20 Dumps](#)

[1Z0-1033-20 Study Guide](#)

[1Z0-1033-20 Exam
Questions](#)