

1Z0-816^{Q&As}

Java SE 11 Programmer II

Pass Oracle 1Z0-816 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/1z0-816.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which statement about a functional interface is true?

- A. It must be defined with the public access modifier.
- B. It must be annotated with @FunctionalInterface.
- C. It is declared with a single abstract method.
- D. It is declared with a single default method.
- E. It cannot have any private methods and static methods.

Correct Answer: C

Reference: <https://www.geeksforgeeks.org/functional-interfaces-java/>

QUESTION 2

Given:

```
public class SerializedMessage implements Serializable {
    String message;
    LocalDateTime createdAt;
    transient LocalDateTime updatedAt;
    SerializedMessage(String message) {
        this.message = message;
        this.createdAt = LocalDateTime.now();
    }
    private void readObject (ObjectInputStream in) {
        try {
            in.defaultReadObject();
            this.updatedAt = LocalDateTime.now();
        } catch (IOException | ClassNotFoundException e) {
            e.printStackTrace();
        }
    }
}
```

When is the readObject method called?

- A. before this object is deserialized
- B. after this object is deserialized
- C. before this object is serialized

- D. The method is never called.
- E. after this object is serialized

Correct Answer: B

Reference: <https://www.oracle.com/technical-resources/articles/java/javaserial.html>

QUESTION 3

Given:

```
public class Main {
    public static void main(String[] args) {
        var numbers = List.of(1,2,3,4,5,6,7,8,9,10);
        Optional<Integer> result = numbers.stream().filter(x -> x % 3 != 0).reduce((i, j)
-> i + j);
        result.ifPresent(System.out::print); // line 1
    }
}
```

Which is true about line 1?


- A. If the value is not present, a NoSuchElementException is thrown at run time.
- B. It always executes the System.out::print statement.
- C. If the value is not present, a NullPointerException is thrown at run time.
- D. If the value is not present, nothing is done.

Correct Answer: D

```
1 import java.util.*;
2 import java.io.*;
3 import java.lang.Thread;
4 import java.util.ArrayList;
5 import java.util.LinkedList;
6 import java.util.List;
7 import java.util.function.Consumer;
8 import java.util.stream.Stream;
9 import java.util.stream.IntStream;
10 import java.util.Optional;
11
12
13 public class Main {
14     public static void main(String[] args) {
15         var numbers = List.of(1,2,3,4,5,6,7,8,9,10);
16         Optional<Integer> result = numbers.stream().filter(x -> x % 3 != 0).reduce((i, j) -> i + j);
17
18     }
19 }
```

Result

CPU Time: 0.18 sec(s), Memory: 33380 kilobyte(s)



QUESTION 4

Given the code fragment:

```
var pool = Executors.newFixedThreadPool(5);
```

```
Future outcome = pool.submit(() -> 1);
```

Which type of lambda expression is passed into submit()?

- A. java.lang.Runnable
- B. java.util.function.Predicate
- C. java.util.function.Function
- D. java.util.concurrent.Callable

Correct Answer: D

Reference: <https://www.codota.com/code/java/methods/java.util.concurrent.Executors/newFixedThreadPool>

QUESTION 5

Given:

```
// line 1
List<String> fruits = new ArrayList<>(List.of("apple", "orange", "banana"));
fruits.replaceAll(function);
```

Which statement on line 1 enables this code fragment to compile?

- A. Function function = String::toUpperCase;
- B. UnaryOperator function = s -> s.toUpperCase();
- C. UnaryOperator function = String::toUpperCase;
- D. Function function = m -> m.toUpperCase();

Correct Answer: C

```
1
2 import java.io.*;
3 import java.util.*;
4 import java.util.stream.Stream;
5 import java.util.function.Function;
6 import java.util.function.UnaryOperator;
7
8 class Hello {
9     public static void main(String[] args) {
10
11         UnaryOperator<String> function = String::toUpperCase;
12         List<String> fruits = new ArrayList<>(List.of("apple", "orange", "banana"));
13         fruits.replaceAll(function);
14
15     }
16 }
17
```

[1Z0-816 PDF Dumps](#)

[1Z0-816 Study Guide](#)

[1Z0-816 Braindumps](#)