

# 201<sup>Q&As</sup>

TMOS Administration

## Pass F5 201 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/201.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by F5 Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

A BIG-IP Administrator needs to purchase new licenses for a BIG-IP appliance.

The administrator needs to know if a module is licensed and the memory requirement for that module.

Where should the administrator view this information in the System menu?

- A. Resource Provisioning
- B. Configuration > Device
- C. Software Management
- D. Configuration >OVSDB

Correct Answer: A

---

**QUESTION 2**

What is required for a virtual server to support clients whose traffic arrives on the internal VLAN and pool members whose traffic arrives on the external VLAN?

- A. That support is never available.
- B. The virtual server must be enabled for both VLANs.
- C. The virtual server must be enabled on the internal VLAN.
- D. The virtual server must be enabled on the external VLAN.

Correct Answer: C

---

**QUESTION 3**

Which two statements are true about NATs? (Choose two.)

- A. NATs support UDP, TCP, and ICMP traffic.
- B. NATs can be configured with mirroring enabled or disabled.
- C. NATs provide a one-to-one mapping between IP addresses.
- D. NATs provide a many-to-one mapping between IP addresses.

Correct Answer: AC

---

**QUESTION 4**

A BIG-IP Administrator needs to remove a pool specific health monitor. There is a pool named Best Pool with two members, one named Best pool member and one named Best pool member2. In the Local Traffic section of the administrative GUI, which steps should the BIG-IP Administrator take to remove a pool level monitor?

- A. Pool > Pool List > Best Pool > Members > Health Monitors
- B. Nodes > Node List > Best \_pool\_member1 > Health Monitors
- C. Monitors > Monitor Name > Instances
- D. Pool > Pool List > Best Pool > Health Monitors

Correct Answer: D

---

#### QUESTION 5

Users report that traffic is negatively affected every time a BIG-IP device fails over. The traffic becomes stabilized after a few minutes.

What should the BIG-IP Administrator do to reduce the impact of future failovers?

- A. Enable Failover Multicast Configuration
- B. Set up Failover Method to HA Order
- C. Configure MAC Masquerade
- D. Configure a global SNAT Listener

Correct Answer: C

[201 PDF Dumps](#)

[201 Study Guide](#)

[201 Exam Questions](#)