300-170^{Q&As}

Implementing Cisco Data Center Virtualization and Automation

Pass Cisco 300-170 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4lead.com/300-170.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

365 Days Free Update

800,000+ Satisfied Customers

QUESTION 1

```
apic# configure
apic(config)# vmware-domain cisco
apic(config-vmware)# configure-avs
apic(config-vmware-avs)# firewall mode enable
```

Refer to the exhibit. What is the result of the configuration?

A. It enforces the distributed firewall.

B. It requires a reboot of the Cisco APIC before enabling the firewall rules.

C. It removes firewall information from the Cisco AVS.

D. It monitors all the TCP traffic without enforcing the firewall rules.

Correct Answer: A

QUESTION 2

Which two tenants are configured by default in Cisco ACI? (Choose two.)

A. common

B. VRF

C. Cisco

D. customer

E. mgmt

Correct Answer: AE

QUESTION 3

Which statement about POAP temporary licensing is true?

A. It is invoked by using the license grace-period command.

B. It is enabled automatically and is valid for 60 days.

C. It is invoked by using the license install command.

D. It is enabled automatically and is valid for 30 days.

Correct Answer: A

Reference: http://www.cisco.com/c/en/us/td/docs/switches/datacenter/nexus7000/sw/fundamentals/config/cisco_nexus7000_fundamentals_config_guide_8x/Using_PowerOn_Auto_Provisioning.pdf

---

QUESTION 4

You have a Cisco Nexus device that is configured to use a RADIUS server. What occurs when local RBAC user account and RADIUS roles exist simultaneously?

A. Only rules that are in local roles and the RADIUS roles are applied

B. Rules from local account and the RADIUS roles are merged

C. Only rules from the local roles are applied

D. Only rules from the RADIUS roles are applied

Correct Answer: D

QUESTION 5

You are implementing multicast routing between bridge domains for a client who is running ACI version 3.0 with Nexus ACI first-generation switches. What is required for multicast to operate?

A. an external router to perform multicast routing between the bridge domains

B. bootstrap router for RP to group mapping

C. PIM Any Source Multicast protocol

D. PIM Source Specific Multicast protocol

Correct Answer: A

[300-170 PDF Dumps](link)   [300-170 VCE Dumps](link)   [300-170 Practice Test](link)

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications.
You can view Vendor list of All Certification Exams offered:

https://www.pass4lead.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: