



300-207^{Q&As}

Implementing Cisco Threat Control Solutions

Pass Cisco 300-207 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4lead.com/300-207.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which two options are features of the Cisco Email Security Appliance? (Choose two.)

- A. Cisco Anti-Replay Services
- B. Cisco Destination Routing
- C. Cisco Registered Envelope Service
- D. Cisco IronPort SenderBase Network

Correct Answer: CD

QUESTION 2

Which three pieces of information are required to implement transparent user identification using Context Directory Agent? (Choose three.)

- A. the server name of the global catalog domain controller
- B. the server name where Context Directory Agent is installed
- C. the backup Context Directory Agent
- D. the primary Context Directory Agent
- E. the shared secret
- F. the syslog server IP address

Correct Answer: BDE

QUESTION 3

Which Cisco Web Security Appliance deployment mode requires minimal change to endpoint devices?

- A. Transparent Mode
- B. Explicit Forward Mode
- C. Promiscuous Mode
- D. Inline Mode

Correct Answer: A

QUESTION 4



Which Cisco Security IntelliShield Alert Manager Service component mitigates new botnet, phishing, and web-based threats?

- A. the IntelliShield Threat Outbreak Alert
- B. IntelliShield Alert Manager vulnerability alerts
- C. the IntelliShield Alert Manager historical database
- D. the IntelliShield Alert Manager web portal
- E. the IntelliShield Alert Manager back-end intelligence engine

Correct Answer: A

QUESTION 5

Which option describes how the native VLAN is set up on an IPS sensor when VLAN groups are used in an inline deployment of the sensor?

- A. The sensor looks at the native VLAN setup on the switch to determine the correct native VLAN to use.
- B. The sensor does not care about VLANs.
- C. A default VLAN variable must be associated with each physical interface on the sensor.
- D. There is no way to set this, so you need to tag all traffic.
- E. ISL links are only supported.

Correct Answer: C

[Latest 300-207 Dumps](#)

[300-207 VCE Dumps](#)

[300-207 Study Guide](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.pass4lead.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4lead, All Rights Reserved.