

300-430^{Q&As}

Implementing Cisco Enterprise Wireless Networks (ENWLSI)

Pass Cisco 300-430 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/300-430.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

An engineer is following the proper upgrade path to upgrade a Cisco AireOS WLC from version 7.3 to 8.9. Which two ACLs for Cisco CWA must be configured when upgrading from the specified codes? (Choose two.)

- A. Permit 0.0.0.0 0.0.0.0 UDP any any
- B. Permit 0.0.0.0 0.0.0.0 any DNS any
- C. Permit 0.0.0.0 0.0.0.0 UDP DNS any
- D. Permit 0.0.0.0 0.0.0.0 UDP any DNS
- E. Permit any any any

Correct Answer: CD

<https://www.cisco.com/c/en/us/support/docs/security/identity-services-engine/115732-central-web-auth-00.html>

QUESTION 2

You plan to implement Cisco Identity Based Networking Services on a Cisco Catalyst 3850 Series Switch. Which switch command is required when configuring downloadable ACLs?

- A. authentication display new-style
- B. ip device tracking
- C. dot1x system-auth-control
- D. aaa session-id common

Correct Answer: B

QUESTION 3

Which CLI command do you use to shut down the 2.4 GHz radio of the Floor1_AP1 AP on a Cisco 3850 Switch?

- A. ap name Floor1_AP1 dot11 shutdown 24ghz
- B. ap name Floor1_AP1 dot11 5ghz shutdown
- C. ap name Floor1 AP1 dot11 24ghz shutdown
- D. ap name Floor1_AP1 shutdown dot11 24ghz

Correct Answer: C

QUESTION 4

An engineer must use Cisco AVC on a Cisco WLC to prioritize Cisco IP cameras that use the wireless network. Which element do you configure in a rule?

- A. permit-ACL
- B. WMM required
- C. mark
- D. rate-limit

Correct Answer: C

https://www.cisco.com/c/en/us/td/docs/wireless/controller/technotes/8-8/AVC_8point8_dg.html

QUESTION 5

An IT team is growing quickly and needs a solution for management device access. The solution must authenticate users from an external repository instead of the current local on the WLC, and it must also identify the user and determine what level of access users should have.

Which protocol do you recommend to achieve these goals?

- A. network policy server
- B. RADIUS
- C. TACACS+
- D. LDAP

Correct Answer: C

https://www.cisco.com/c/en/us/td/docs/switches/lan/Denali_161/ConfigExamples_Technotes/Techzone_Articles/Example_and_Technotes_Denali_16_1_1/Example_and_Technotes_Denali_16_1_1_chapter_010110.pdf <https://community.cisco.com/t5/wireless-mobility-documents/wlc-and-acx-5-x-tacacs-configuration-example-web-authentication/tap/3120681>

[300-430 PDF Dumps](#)

[300-430 VCE Dumps](#)

[300-430 Braindumps](#)