

300-625^{Q&As}

Implementing Cisco Storage Area Networking (DCSAN)

Pass Cisco 300-625 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/300-625.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which two components are required for successful MDS USB POAP (Choose two.)

- A. NTFS formatted USB drive
- B. USB drive in port 1
- C. script named poap_script.pl
- D. ENTERPRISE_PKG license
- E. system and kickstart images

Correct Answer: CE

QUESTION 2

Which Cisco NX-OS command displays the VSAN that is associated with each FCID?

- A. show fcdomain
- B. show fc2 plugi
- C. show vsan database
- D. show flogi database

Correct Answer: A

QUESTION 3

DRAG DROP

Drag and drop the DCNM configuration tasks from the left onto the correct tools on the right.

Select and Place:

- View the values for more than one switch at a time.
- Display fabric extenders.
- Configure vFC interfaces.
- Use the End to End Connectivity Analysis tool to verify connections.
- Configure zones for multiple VSANs.

Device Manager

[Empty box]

[Empty box]

[Empty box]

Cisco DCNM-SAN Client

[Empty box]

[Empty box]

Correct Answer:

[Empty box]

[Empty box]

[Empty box]

[Empty box]

[Empty box]

[Empty box]

Device Manager

Configure vFC interfaces.

Configure zones for multiple VSANs.

View the values for more than one switch at a time.

Cisco DCNM-SAN Client

Use the End to End Connectivity Analysis tool to verify connections.

Display fabric extenders.

QUESTION 4

Which configuration is always required when running the setup utility on a Cisco MDS 9000 Series Switch?

- A. administrator password
- B. management IP address
- C. active NTP server
- D. active default gateway

Correct Answer: A

QUESTION 5

DRAG DROP

Drag and drop the FLOGI parameters from the left onto the descriptions from which they were-derived on the right.

Select and Place:

fWWN	VSAN-based sWWN of the NPV device
IP address	IP address of the NPV device
symbolic node name	fWWN of the F Port on the NPV core switch
nWWN	NPV switch name
pWWN	fWWN of the NP Port

Correct Answer:

	nWWN	
	IP address	
	fWWN	ch
	symbolic node name	
	pWWN	

Reference: https://www.cisco.com/en/US/docs/storage/san_switches/mds9000/sw/rel_3_x/configuration/guides/cli_3_3_1/npv.html#wp1502832

[300-625 PDF Dumps](#)

[300-625 VCE Dumps](#)

[300-625 Study Guide](#)