

# 300-715<sup>Q&As</sup>

Implementing and Configuring Cisco Identity Services Engine (SISE)

## Pass Cisco 300-715 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/300-715.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

Which two components are required for creating a Native Supplicant Profile within a BYOD flow? (Choose two )

- A. Windows Settings
- B. Connection Type
- C. iOS Settings
- D. Redirect ACL
- E. Operating System

Correct Answer: BE

[https://www.cisco.com/c/en/us/td/docs/security/ise/2-1/admin\\_guide/b\\_ise\\_admin\\_guide\\_21/b\\_ise\\_admin\\_guide\\_20\\_chapter\\_010101.html#reference\\_21024A3B2B27427EAC78495E56962729](https://www.cisco.com/c/en/us/td/docs/security/ise/2-1/admin_guide/b_ise_admin_guide_21/b_ise_admin_guide_20_chapter_010101.html#reference_21024A3B2B27427EAC78495E56962729)

---

**QUESTION 2**

An engineer must configure Cisco ISE to provide internet access for guests in which guests are required to enter a code to gain network access. Which action accomplishes the goal?

- A. Configure the hotspot portal for guest access and require an access code.
- B. Configure the sponsor portal with a single account and use the access code as the password.
- C. Configure the self-registered guest portal to allow guests to create a personal access code.
- D. Create a BYOD policy that bypasses the authentication of the user and authorizes access codes.

Correct Answer: A

Reference:

[https://www.cisco.com/c/en/us/td/docs/security/ise/2-4/admin\\_guide/b\\_ISE\\_admin\\_guide\\_24/m\\_ise\\_guest.html](https://www.cisco.com/c/en/us/td/docs/security/ise/2-4/admin_guide/b_ISE_admin_guide_24/m_ise_guest.html)

---

**QUESTION 3**

An administrator is configuring a Cisco ISE posture agent in the client provisioning policy and needs to ensure that the posture policies that interact with clients are monitored, and end users are required to comply with network usage rules Which two resources must be added in Cisco ISE to accomplish this goal? (Choose two)

- A. AnyConnect
- B. Supplicant
- C. Cisco ISE NAC
- D. PEAP

E. Posture Agent

Correct Answer: AE

[https://www.cisco.com/c/en/us/td/docs/security/vpn\\_client/anyconnect/anyconnect40/administration/guide/b\\_AnyConnect\\_Administrator\\_Guide4-0/configure-posture.html](https://www.cisco.com/c/en/us/td/docs/security/vpn_client/anyconnect/anyconnect40/administration/guide/b_AnyConnect_Administrator_Guide4-0/configure-posture.html) [https://www.cisco.com/c/en/us/td/docs/security/ise/2-4/admin\\_guide/b\\_ISE\\_admin\\_guide\\_24/m\\_configure\\_client\\_provisioning.html#task\\_D1C2E8ECE1D54D259C01BCBF0A5822F1](https://www.cisco.com/c/en/us/td/docs/security/ise/2-4/admin_guide/b_ISE_admin_guide_24/m_configure_client_provisioning.html#task_D1C2E8ECE1D54D259C01BCBF0A5822F1)

---

#### QUESTION 4

Which two actions occur when a Cisco ISE server device administrator logs in to a device? (Choose two.)

- A. The device queries the internal identity store.
- B. The Cisco ISE server queries the internal identity store.
- C. The device queries the internal identity store.
- D. The Cisco ISE server queries the external identity store.
- E. The device queries the Cisco ISE authorization server.

Correct Answer: AD

---

#### QUESTION 5

A network administrator wants to use dynamic VLAN assignment from Cisco ISE. Which option must be configured on the switch to support this?

- A. AAA authentication
- B. VTP
- C. DTP
- D. AAA authorization

Correct Answer: D

[Latest 300-715 Dumps](#)

[300-715 VCE Dumps](#)

[300-715 Practice Test](#)