

300-715^{Q&As}

Implementing and Configuring Cisco Identity Services Engine (SISE)

Pass Cisco 300-715 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/300-715.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which type of identity store allows for creating single-use access credentials in Cisco ISE?

- A. OpenLDAP
- B. Local
- C. PKI
- D. RSA SecurID

Correct Answer: D

Reference: https://www.cisco.com/en/US/docs/security/ise/1.0/user_guide/ise10_man_id_stores.html

QUESTION 2

When planning for the deployment of Cisco ISE, an organization's security policy dictates that they must use network access authentication via RADIUS. It also states that the deployment provides an adequate amount of security and visibility for the hosts on the network. Why should the engineer configure MAB in this situation?

- A. The Cisco switches only support MAB.
- B. MAB provides the strongest form of authentication available.
- C. The devices in the network do not have a supplicant.
- D. MAB provides user authentication.

Correct Answer: C

QUESTION 3

DRAG DROP

An organization wants to implement 802.1X and is debating whether to use PEAP-MSCHAPv2 or PEAP-EAP-TLS for authentication. Drag the characteristics on the left to the corresponding protocol on the right.

Select and Place:

uses username and password for authentication	PEAP-MSCHAPv2
uses certificates for authentication	
changes credentials through the admin portal	
supports fragmentation after the tunnel is established	PEAP-EAP-TLS
uses the X.509 format	
supports auto-enrollment for obtaining credentials	

Correct Answer:

	PEAP-MSCHAPv2
	PEAP-EAP-TLS

	uses username and password for authentication
	changes credentials through the admin portal
	supports fragmentation after the tunnel is established

	uses certificates for authentication
	uses the X.509 format
	supports auto-enrollment for obtaining credentials

QUESTION 4

An engineer is configuring 802.1X and is testing out their policy sets. After authentication, some endpoints are given an access-reject message but are still allowed onto the network. What is causing this issue to occur?

- A. The switch port is configured with authentication event server dead action authorize vlan.
- B. The authorization results for the endpoints include a dACL allowing access.

- C. The authorization results for the endpoints include the Trusted security group tag.
- D. The switch port is configured with authentication open.

Correct Answer: D

QUESTION 5

An engineer must configure Cisco ISE to provide internet access for guests in which guests are required to enter a code to gain network access. Which action accomplishes the goal?

- A. Configure the hotspot portal for guest access and require an access code.
- B. Configure the sponsor portal with a single account and use the access code as the password.
- C. Configure the self-registered guest portal to allow guests to create a personal access code.
- D. Create a BYOD policy that bypasses the authentication of the user and authorizes access codes.

Correct Answer: A

Reference:

https://www.cisco.com/c/en/us/td/docs/security/ise/2-4/admin_guide/b_ISE_admin_guide_24/m_ise_guest.html

[300-715 PDF Dumps](#)

[300-715 Study Guide](#)

[300-715 Braindumps](#)