

300-715^{Q&As}

Implementing and Configuring Cisco Identity Services Engine (SISE)

Pass Cisco 300-715 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/300-715.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

An engineer tests Cisco ISE posture services on the network and must configure the compliance module to automatically download and install on endpoints. Which action accomplishes this task for VPN users?

- A. Push the compliance module from Cisco FTD prior to attempting posture.
- B. Use a compound posture condition to check for the compliance module and download, if needed.
- C. Configure the compliance module to be downloaded from within the posture policy.
- D. Create a Cisco AnyConnect configuration and Client Provisioning policy within Cisco ISE.

Correct Answer: D

Reference: https://www.cisco.com/c/en/us/td/docs/security/ise/2-4/admin_guide/b_ISE_admin_guide_24/m_configure_client_provisioning.html

QUESTION 2

An engineer is creating a new authorization policy to give the endpoints access to VLAN 310 upon successful authentication. The administrator tests the 802.1X authentication for the endpoint and sees that it is authenticating successfully.

What must be done to ensure that the endpoint is placed into the correct VLAN?

- A. Configure the switchport access vlan 310 command on the switch port.
- B. Ensure that the security group is not preventing the endpoint from being in VLAN 310.
- C. Add VLAN 310 in the common tasks of the authorization profile.
- D. Ensure that the endpoint is using the correct policy set.

Correct Answer: C

QUESTION 3

An engineer is configuring static SGT classification. Which configuration should be used when authentication is disabled and third-party switches are in use?

- A. VLAN to SGT mapping
- B. IP Address to SGT mapping
- C. L3IF to SGT mapping
- D. Subnet to SGT mapping

Correct Answer: B

<https://community.cisco.com/t5/security-knowledge-base/segmentation-strategy/ta-p/3757424>:

"The method of sending out IP to SGT mappings from ISE is particularly useful if the access switch does not support TrustSec"

QUESTION 4

An administrator replaced a PSN in the distributed Cisco ISE environment. When endpoints authenticate to it, the devices are not getting the right profiles or attributes and as a result, are not hitting the correct policies. This was working correctly on the previous PSN. Which action must be taken to ensure the endpoints get identified?

- A. Verify that the MnT node is tracking the session.
- B. Verify the shared secret used between the switch and the PSN.
- C. Verify that the profiling service is running on the new PSN.
- D. Verify that the authentication request the PSN is receiving is not malformed.

Correct Answer: C

QUESTION 5

Client provisioning resources can be added into the Cisco ISE Administration node from which three of these? (Choose three.)

- A. FTP
- B. TFTP
- C. www-cisco.com
- D. local disk
- E. Posture Agent Profile

Correct Answer: CDE

[Latest 300-715 Dumps](#)

[300-715 Study Guide](#)

[300-715 Braindumps](#)