

# 300-815<sup>Q&As</sup>

Implementing Cisco Advanced Call Control and Mobility Services  
(CLACCM)

## Pass Cisco 300-815 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/300-815.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

An engineer is troubleshooting an intersite call between two endpoints where the call fails and the message “Not Enough Bandwidth” is displayed. G.729 codec is in use on both sites. First, calls are being properly routed, and the issue happens after the third call is established and the bandwidth utilization between the two sites is under 50%. Which configuration in Cisco UCM must be adjusted to resolve the issue?

- A. transcoder
- B. location
- C. route pattern
- D. translation pattern

Correct Answer: B

**QUESTION 2**

Refer to the exhibit.

```
voice hunt-group 1 
  phone-display
  final 7777
  list 1002,1003,1005,1006,1010
  hops 3
  pilot 2222
```

DN 1003 was the last to ring during the most recent call. Which hunting method ensures that DN 1005 is presented with the next call when the hunt pilot is dialed?

- A. sequential
- B. call-blast
- C. peer
- D. parallel

Correct Answer: C

**QUESTION 3**

An administrator manages an environment with mobile users who commonly move between locations and take IP phones to remote sites. When mobile users are at one of the sites, users report issues with call quality, such as the audio cutting in and out. In addition, the affected area has a low bandwidth connection compared to other sites, so the administrator has put these devices in a region with an inter-region restriction of 8 kbps per call. Which feature must the administrator configure to mitigate the issue?

- A. Location Bandwidth Manager
- B. Extension Mobility
- C. Device Mobility
- D. Extension Mobility Cross Cluster

Correct Answer: A

---

**QUESTION 4**

A support engineer is troubleshooting a voice network. When conducting a search for call setup details related to calling search space issues, which trace files should be investigated?

- A. CallManager traces
- B. CTI Manager traces
- C. Cisco IP Manager Assistant
- D. Call logs

Correct Answer: A

---

**QUESTION 5**

DRAG DROP

Drag and drop the commands from the bottom to the blanks in the code to implement a translation rule to allow only 11 digits to be received over a SIP trunk to a SIP provider. The Cisco UCM is currently sending calls to the Cisco Unified Border Element in E.164 format. Not all options are used.

Select and Place:

```
voice translation-rule 1000
[ ]
!
voice translation-profile STRIP-PLUS
translate [ ] [ ]
```

rule 1 /+/ //	calling
100	rule 1 /\+/ //
called	1000

Correct Answer:

```
voice translation-rule 1000
rule 1 /+/ //
!
voice translation-profile STRIP-PLUS
translate called 1000
```

	calling
100	rule 1 /\+/ //

Reference: <https://www.cisco.com/c/en/us/support/docs/voice/call-routing-dial-plans/61083-voice-transla-rules.html>

[300-815 VCE Dumps](#)

[300-815 Exam Questions](#)

[300-815 Braindumps](#)