

# 300-825<sup>Q&As</sup>

Implementing Cisco Collaboration Conferencing (CLCNF)

## Pass Cisco 300-825 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/300-825.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

```
Content-Type: application/sdp Content-Length: 4938 v=0 o=Acano 0 0 IN IP4 10.0.101.120 s=c=IN IP4 10.0.101.120
b=CT:16 t=0 0 m=audio 50262 RTP/AVP 108 107 109 110 9 99 111 100 104 103 0 8 15 102 18 13 118 101 a=crypto:1
AEAD_AES_128_GCM *****|2^48 a=crypto:2 AEAD_AES_256_GCM
*****|2^48 a=crypto:3 AES_CM_128_HMAC_SHA1_80
*****|2^48 a=crypto:4 AES_CM_128_HMAC_SHA1_32
*****|2^48 m=video 50264 RTP/AVP 97 116 114 96 34 31 100 121
b=TIAS:16000 a=crypto:1 AEAD_AES_128_GCM *****|2^48 a=crypto:2
AEAD_AES_256_GCM *****|2^48 a=crypto:3
AES_CM_128_HMAC_sha1_80 *****|2^48 a=crypto:4
AES_CM_128_HMAC_sha1_32 *****|2^48 a=content:main a=sendrecv
a=sprop-source:1 count=2;policies=cs:1 a=sprop-simul:1 1 * a=rtcp-fb:* nack pli a=rtcp-fb:* ccm fir a=rtcp-fb:* ccm cisco-
scr a=extmap:1 http://protocols.cisco.com/virtualid a=extmap:2 http://protocols.cisco.com/frame marking a=rtpmap:97
H264/90000 a=fmtp:97 profile-level-id=42800a;max-mpbs=489600;max-fs=8160;max-cpb=4000;max-dpd=4752;max-
fps=6000
```

Refer to the exhibit. Users report that they do not see a high-quality picture on the high-definition endpoints when they call into Cisco Meeting Server. An engineer must extract the SDP that is offered by Cisco Meeting Server from the SIP traces to troubleshoot. What is the cause of this issue?

- A. Cisco Meeting Server is not configured for H.265 to support high-definition video calling.
- B. The AES ciphers are not compatible with high-definition video calling.
- C. The Content-Length value in the SDP does not support high-definition video calling.
- D. The SIP call bandwidth is not at a value that supports high-definition video calling.

Correct Answer: D

**QUESTION 2**

To which Skype for Business service does Cisco Meeting Server send media in dual-homed meetings?

- A. UserServer
- B. ClsAgent
- C. W3SVC
- D. AVMCU

Correct Answer: D

Reference: <https://www.ciscolive.com/c/dam/r/ciscolive/apjc/docs/2019/pdf/BRKCOL-3111.pdf>

**QUESTION 3**

An administrator configures a Call Bridge to record meetings. Which two configuration elements tell the Call Bridge where to find the recording server? (Choose two.)

- A. tenants
- B. IVR
- C. DTMF combination
- D. sipRecorderUri
- E. outbound rules

Correct Answer: AD

Reference: [https://www.cisco.com/c/dam/en/us/td/docs/conferencing/ciscoMeetingServer/Deployment\\_Guide/Version-3-0/Cisco-Meeting-Server-3-0-Single-Combined-Server-Deployment.pdf](https://www.cisco.com/c/dam/en/us/td/docs/conferencing/ciscoMeetingServer/Deployment_Guide/Version-3-0/Cisco-Meeting-Server-3-0-Single-Combined-Server-Deployment.pdf)

---

#### QUESTION 4

An organization wants to ensure that off-premises users can use a browser to join the Cisco Meeting Server web app without needing additional software. What must be included in the Expressway-E certificate to accomplish this goal?

- A. the Call Bridge name as a SAN
- B. the Web Admin interface FQDN as a SAN
- C. the name of each Cisco Meeting Server that is part of the cluster
- D. the Guest account client URI as a SAN

Correct Answer: B

Reference: <https://www.cisco.com/c/en/us/support/docs/conferencing/meeting-server/210800-configure-cms-webrtc-proxy-over-expressw.html>

---

#### QUESTION 5

An engineer configures Cisco Meeting Server as a conference resource for Cisco UCM. Cisco UCM has a secure SIP trunk to Cisco Meeting Server, but the server does not register to Cisco UCM. Which configuration resolves this issue?

- A. Ensure that the SIP trunk from Cisco UCM to Cisco Meeting Server is a secure trunk using port 5061.
- B. Add Cisco Meeting Server to the Cisco UCM SIP trunk with an IP address and not an FQDN.
- C. Set the Web Admin port on the Conference Bridge settings to match Cisco Meeting Server.
- D. Configure an MRGL that contains Cisco Meeting Server to be associated with device pools.

Correct Answer: D

Reference: <https://www.cisco.com/c/en/us/support/docs/conferencing/meeting-server/213820-configure-cisco-meeting-server-and-cucm.html>

---

[Latest 300-825 Dumps](#)

[300-825 PDF Dumps](#)

[300-825 Exam Questions](#)