

350-801^{Q&As}

Implementing and Operating Cisco Collaboration Core Technologies
(CLCOR)

Pass Cisco 350-801 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/350-801.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which configuration on Cisco Unified Communications Manager is required for SIP MWI to work?

- A. The line partition must be inside the inbound CSS assigned to the CUC SIP trunk.
- B. The line partition must be inside the rerouting CSS assigned to the Cisco Unity Connection SIP trunk.
- C. Set the "Enable message waiting indicator" on the part group.
- D. Assign a MWI extension on the mailbox.

Correct Answer: A

The line partition must be inside the inbound CSS assigned to the CUC SIP trunk. This ensures that the SIP MWI messages are sent to the correct destination.

The other options are incorrect because:

Assigning an MWI extension on the mailbox is not required for SIP MWI to work. The line partition does not need to be inside the rerouting CSS assigned to the Cisco Unity Connection SIP trunk.

Setting the "Enable message waiting indicator" on the port group is not required for SIP MWI to work.

QUESTION 2

A collaboration engineer troubleshoots issues with a Cisco IP Phone 7800 Series. The IPv4 address of the phone is reachable via ICMP and HTTP, and the phone is registered to Cisco UCM. However, the engineer cannot reach the CLI of the phone. Which two actions in Cisco UCM resolve the issue? (Choose two.)

- A. Enable Settings Access under Product Specific Configuration Layout in Cisco UCM.
- B. Enable FIPS Mode under Product Specific Configuration Layout in Cisco UCM.
- C. Enable SSH Access under Product Specific Configuration Layout in Cisco UCM.
- D. Set a username and password under Secure Shell Information in Cisco UCM.
- E. Disable Web Access under Product Specific Configuration Layout in Cisco UCM.

Correct Answer: CD

Enable ssh for phone, and then setup username and password so that engineer can login to phone via CLI

QUESTION 3

Refer to the exhibit. A collaboration engineer adds an analog gateway to a Cisco UCM cluster. The engineer chooses MGCP over SCCP as the gateway protocol.

```
1 CUBE_1(config)# dial-peer voice 10 voip
2 CUBE_1(config-dial-peer)# session target ipv4:10.10.11.12
3 CUBE_1(config-dial-peer)# session protocol sipv2
4 CUBE_1(config-dial-peer)# dtmf-relay rtp-nte
5 CUBE_1(config-dial-peer)# codec g729r8
6 CUBE_1(config-dial-peer)# end
7
8 CUBE_2(config)# dial-peer voice 11 voip
9 CUBE_2(config-dial-peer)# session target ipv4:10.10.11.11
10 CUBE_2(config-dial-peer)# session protocol sipv2
11 CUBE_2(config-dial-peer)# dtmf-relay rtp-nte
12 CUBE_1(config-dial-peer)# codec g729br8
13 CUBE_2(config-dial-peer)# end
```



Which two actions ensure that the gateway registers? (Choose two.)

- A. Delete and re-add the gateway configuration in Cisco UCM.
- B. Enter "mgcp" on the gateway in configuration mode.
- C. Enter "no sccp" on the gateway in configuration mode.
- D. Enter "ccm-manager config" on the gateway in configuration mode.
- E. Enter "ccm-manager mgcp" on the gateway in configuration mode.

Correct Answer: BE

Reference: <https://community.cisco.com/t5/unified-communications/cisco-router-2901-mgcp-x-callmanager-9-1-1/td-p/2419551>

QUESTION 4

An engineer must configure an MGCP gateway and register it to Cisco Unified Communications Manager. Which prerequisite must be met before applying the gateway commands to enable MGCP?

- A. The MGCP gateway and the Cisco Unified CM must be able to communicate over ports 5060 and 5061.
- B. Cisco Unified CM and the MGCP gateway must utilize the SIP OPTIONS ping feature to monitor status.

C. The MGCP gateway must have voice service VoIP configured.

D. The MGCP gateway and the Cisco Unified CM must be able to communicate over ports 2427, 2428, and 2727.

Correct Answer: D

Reference: https://www.cisco.com/c/en/us/td/docs/ios/voice/cminterop/configuration/guide/12_4t/vc_12_4t_book/vc_ucm_mgcp_gw.html

QUESTION 5

Which Cisco Unified CM service is installed by default and authenticates certificates on behalf of IP phones and other endpoints?

A. Cisco CTL Provider

B. Cisco Certificate Authority Proxy Function

C. Cisco Trust Verification

D. Cisco CallManager

E. Cisco TFTP

Correct Answer: C

[350-801 PDF Dumps](#)

[350-801 VCE Dumps](#)

[350-801 Study Guide](#)