

3605^{Q&As}

Avaya Ethernet Routing Switch Implementation and Maintenance Exam

Pass Avaya 3605 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/3605.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

A technician is configuring the core of a Converged Campus network, and is adding a backup-master configuration to an existing Virtual Router Redundancy

Protocol (VRRP) configuration for a VLAN that extends to the edge switches.

Which benefit is expected from the Addition of backup-master?

- A. reduced traffic on the IST
- B. reduced traffic on the uplink ports
- C. redundant default gateways for host devices
- D. faster switchover time

Correct Answer: D

QUESTION 2

Refer to the exhibit.

```

-----
Cisco IOS XE Software: (x86_64) cat9k
-----
Cisco IOS XE Software: Time: Sun Feb 12 11:04:56 UTC MST
-----
#
#asic info :
# SlotNum|Name      |CardType   |MdaType    |Parts Description
#
# Slot 1   --      0x00000001
# Slot 2 8683XLR  0x24334103 0x00000000 RSP=25 CLUE=2  F2I=4 F2E=3  FTMUX=17 CC=
3 FOQ=267 DPC=194 BMC=776 PIM=0 MAC=0
# Slot 3   --      0x00000001
# Slot 4 8648GTR  0x24220130 0x00000000 RSP=25 CLUE=2  F2I=4 F2E=3  FTMUX=17 CC=
3 FOQ=267 DPC=194 BMC=776 PIM=3 MAC=3
# Slot 5 8895SF   0x200e1100 0x00000000 CPU: BDLB=21 glue=14 SFM: OP=3 TMUX=2
SWIP=23 FAD=16 CF=238
# Slot 6   --      0x00000001
8600-A1:5>
    
```

Based on the command line output shown in the exhibit, how many Gigabit Ethernet ports are available on this Ethernet Routing Switch (ERS) 8600?

- A. 3
- B. 48
- C. 52
- D. 83

Correct Answer: B

QUESTION 3

Before enabling IP Source through Device Manager, which two conditions must be met on the system?

- A. Dynamic Host Control Protocol (DHCP) snooping enabled globally.
- B. EAPOL must be enabled.
- C. The bsSourceGuardConfigMode MIB object must be removed.
- D. The port is an untrusted DHCP snooping and dynamic ARP Inspection port.

Correct Answer: AD

QUESTION 4

Which CLI command is used to validate that synchronization for High Availability mode is set correctly?

- A. Show ha
- B. Show ha-all
- C. Show ha-state
- D. Show ha-sync

Correct Answer: C

QUESTION 5

Traceout allows a route to be traced to a network using an Ethernet Routing Switch (ERS) 8600 CLI command. In the command output, the possible range of `w\` values is 1-255.

The `w\` value represents wait time for what?

- A. Start of command execution
- B. Time to live
- C. Per probe
- D. Completion of traceout report

Correct Answer: C

[3605 PDF Dumps](#)

[3605 Exam Questions](#)

[3605 Brindumps](#)