

3V0-21.21^{Q&As}

Advanced Design VMware vSphere 7.x

Pass VMware 3V0-21.21 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/3v0-21-21.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

The Chief Operating Officer (COO) at an organization raises concerns that their virtual infrastructure environment is vulnerable. Recently, a security-related issue with a virtual machine caused all management services to become unavailable. No budget is available in the short term for additional platform investment. An architect is asked to review the current environment and make recommendations to mitigate concerns.

A virtualization administrator has provided the following details: There is a single four node cluster of ESXi servers. There are two, Layer 2, physical network switches connecting resources. The data center network is presented as a single /16 subnet.

Given the information provided, which functional requirement should the architect include in the design to mitigate the COO's concerns?

- A. The virtual infrastructure environment must connect application virtual machines and management services to new physical network switches.
- B. The virtual infrastructure environment must connect application virtual machines and management services to separate distributed virtual switches (DVS).
- C. The virtual infrastructure environment must connect application virtual machines and management services to separate VLANs.
- D. The virtual infrastructure environment must connect management services to a vSphere standard switch (VSS).

Correct Answer: D

QUESTION 2

An architect is designing a VMware solution for a customer to meet the following requirements:

The solution must use investments in existing storage array that supports both block and file storage.

The solution must support the ability to migrate workloads between hosts within a cluster.

The solution must support resource management priorities.

The solution must support the ability to connect virtual machines directly to LUNs.

The solution should use existing 32G fabric infrastructure.

There is no budget for additional physical hardware.

Which design decision should the architect make to meet these requirements?

- A. The ESXi hosts will leverage Fibre Channel (FC).
- B. The ESXi hosts will leverage iSCSI.
- C. The ESXi hosts will leverage Fibre Channel over Ethernet (FCoE).
- D. The ESXi hosts will leverage NFS.

Correct Answer: A

QUESTION 3

An architect is tasked with designing a greenfield VMware software-defined data center (SDDC) solution that will be used to deliver a private cloud service for a customer.

During the initial meeting with the service owner and business sponsor, the customer has provided the following information to help inform the design:

The solution must initially support the concurrent running of 300 production and 600 development virtual machines.

The production environment should be delivered across two geographically dispersed data centers.

The development environment must be vSphere-based but does not have to be deployed on-premises.

The two data centers are connected to each other through multiple diversely routed, high bandwidth and low latency links.

The customer's server hardware standard document states that all virtual infrastructure hosts must be based on blade architecture only.

The service owner has said that is important to ensure that neither the availability target of 99.5% nor the resource capacity is affected when the operations team completes maintenance activities, such as the monthly software patching and ad-hoc hardware break/fix.

All virtual machine backups must be completed using the existing backup service.

The recovery time objective (RTO) for the service is four hours.

The recovery point objective (RPO) of the service is 24 hours.

Given the information from the customer, which two would be classified as assumptions within the design? (Choose two.)

- A. The backup service will store data in a secure facility
- B. The backup service has sufficient capacity for the new requirements
- C. The customer will update their hardware standard to support rack mount servers
- D. All virtual machines will be deployed with the same resource profile for production and development
- E. The clusters will have a minimum redundancy of N+1

Correct Answer: AC

QUESTION 4

During a requirements gathering workshop, the customer provides the following requirement that is pertinent to the design of a new vSphere environment:

The Maximum Tolerable Downtime (MTD) for all Tier 1 applications is one hour.

Which requirement classification is being gathered for the design documentation?

- A. Manageability
- B. Performance
- C. Availability
- D. Recoverability

Correct Answer: C

QUESTION 5

During a requirements gathering workshop, the customer provides the following requirement (REQ) and constraints (CON):

REQ01: The customer is looking for a way to limit database virtual machine (VM) placement to save on CPU licensing costs.

CON01: There is a single cluster with no budget to scale.

CON02: All virtual machines must run on the consolidated cluster.

Which two design decisions should the architect make to meet the customer requirement? (Choose two.)

- A. The solution must use VM-VM anti-affinity rules
- B. The solution must use vSphere DRS in manual mode
- C. The solution must use a vRealize Orchestrator workflow for VM placement
- D. The solution must use VM-Host affinity rules
- E. The solution must use vSphere VM and host DRS groups

Correct Answer: CE
