

3V0-42.20^{Q&As}

Advanced Design VMware NSX-T Data Center

Pass VMware 3V0-42.20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/3v0-42-20.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

An architect is helping an organization with the Conceptual Design of an NSX-T Data Center solution.

This information was gathered by the architect during the Discover Task of the Engagement Lifecycle:

Existing hardware will be used in any design proposal.

Network bandwidth cannot be expanded.

Which concept of the Discover Task do these items belong to? (Choose the best answer.)

- A. constraint
- B. requirement
- C. risk
- D. assumption

Correct Answer: A

QUESTION 2

What is a design justification for a solution with 3 NSX Manager nodes deployed in a 4 ESXi cluster Management Cluster? (Choose the best answer.)

- A. NSX Controllers are separated from NSX Managers allowing 6 ESXi servers to host them.
- B. NSX Management Plane and Control Plane will be reduced to a single point of failure.
- C. Compute consumption guarantees NSX Manager nodes can be run on the same ESXi host.
- D. Single point of failure on Control Plane and Management Plane will be mitigated.

Correct Answer: B

QUESTION 3

An architect is helping an organization with the Logical Design of an NSX-T Data Center solution. This information was gathered during the Assessment Phase:

NSX-T will span across two sites for disaster recovery.

Public Load Balancer VIP should be accessible from a secondary site.

Distributed Firewall Policies should be available at a secondary site.

Routing capabilities should be maintained after failure.

NAT capabilities are required.

Which two selections should the architect include in their design? (Choose two.)

- A. Use of the same ISPs across sites.
- B. Use two separate ISPs across sites.
- C. Use MTU to 1550 between sites.
- D. Set MTU to 1550 between sites.
- E. Use IP sets or groups to configure DFW rules.

Correct Answer: AE

Reference: <https://www.vmware.com/content/dam/digitalmarketing/vmware/en/pdf/products/nsx/vmwaremulti-site-solutions-cross-vcenter-nsx-design-guide.pdf>

QUESTION 4

An architect is helping an organization with the Physical Design of an NSX-T Data Center solution.

This information was gathered during the Assessment Phase:

There is a critical application used by the Finance Team.

The critical application has an availability and recoverability SLA of 99.999%.

The critical application is sensitive to network changes.

Which two selections should an architect include in their design? (Choose two.)

- A. Configure Tier-0 gateway for eBGP and ECMP.
- B. Configure Tier-1 gateway for eBGP and ECMP.
- C. Enable BFD on Tier-0 gateway.
- D. Install and configure hosts with 100Gbps physical NICs.
- E. Configure multiple static routes on Tier-1 gateway.

Correct Answer: BD

QUESTION 5

According to the Discover Task of the Engagement Lifecycle, which statement would be classified as a risk? (Choose the best answer.)

- A. Enough power and cooling capacity is available in each rack in the data center.

- B. To retain certification to provide financial services to end customers, PCI-DSS audits need to be passed.
- C. A merger and acquisition process was recently completed and new company on-boarding is not completed.
- D. Due to existing contracts and purchase agreements, the existing server hardware needs to be reused.

Correct Answer: B

[3V0-42.20 VCE Dumps](#)

[3V0-42.20 Practice Test](#)

[3V0-42.20 Braindumps](#)