

4A0-101^{Q&As}

Alcatel-Lucent Interior Routing Protocols and High Availability

Pass Alcatel-Lucent 4A0-101 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/4a0-101.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Alcatel-Lucent Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

What is the source IP address in an OSPF update?

- A. 224.0.0.5
- B. 224.0.0.6
- C. The unicast IP address of the interface the update is sent on
- D. The system address of the router.

Correct Answer: C

QUESTION 2

An interface has a MAC address of 24-16-4d-16-b5-3d. What link-local address will be assigned to this interface?

- A. fe80::2416:4dff:fe16:b53d
- B. fe80::2616:4dff:fe16:b53d
- C. ff80::2416:4dff:fe 16:b53d
- D. ff80::2616:4dff:fe 16:b53d
- E. fd80::2416:4dff:fe16:b53d

Correct Answer: B

QUESTION 3

If two routers running IS-IS protocols are exchanging Hello packets with different authentication types, which of the following statements regarding the adjacency state established between them is true?

- A. Different authentication types are not possible because IS-IS only supports password authentication.
- B. An adjacency will not be formed
- C. The two routers negotiate the authentication type and then reach the up state.
- D. Only an L2 adjacency will form, as long as both routers are L2 capable.

Correct Answer: B

QUESTION 4

Which OSPFv3 LSA is similar to the OSPFv2 Type 5 LSA?

- A. AS External
- B. Inter-Area Prefix
- C. Inter-Area Router
- D. Intra-Area Prefix

Correct Answer: A

QUESTION 5

Click on the exhibit.

R6# show router ospf database

```
=====
OSPF Link State Database (Type : ALL)
=====
```

Type	Area Id	Link State Id	Adv Rtr Id	Age	Sequence	Cksum
Router	0.0.0.0	10.10.10.2	10.10.10.2	347	0x80000009	0xcd9a
Router	0.0.0.0	10.10.10.3	10.10.10.3	347	0x80000005	0xbedd
Router	0.0.0.0	10.10.10.6	10.10.10.6	350	0x80000005	0x233a
Network	0.0.0.0	1.1.1.6	10.10.10.6	346	0x80000002	0xdce5
Summary	0.0.0.0	10.2.4.0	10.10.10.2	441	0x80000002	0x9136
Summary	0.0.0.0	10.10.10.4	10.10.10.2	440	0x80000001	0xc8ed

```
=====
No. of LSAs: 6
=====
```

Given the output shown, which router is the ASBR in this network?

- A. 10.10.10.2
- B. 10.10.10.3
- C. 10.10.10.4
- D. 10.10.10.6
- E. There is no ASBR configured in the network.

Correct Answer: E

[4A0-101 PDF Dumps](#)

[4A0-101 VCE Dumps](#)

[4A0-101 Braindumps](#)