

4A0-M03^{Q&As}

Nokia Mobility Manager

Pass Nokia 4A0-M03 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/4a0-m03.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which of the following statements regarding paging policy is FALSE?

- A. Paging method defines which forwarding path is used to forward the paging message to eNodeBs
- B. Paging policy defines paging procedures used by MME to page an idle UE
- C. Paging timer specifies the time to wait for a response to a paging request message
- D. Paging attempt specifies the number of times MME tries to page a UE before the UE is deemed non-responsive

Correct Answer: A

QUESTION 2

Given the exhibit, the MME is unable to retrieve authentication vector (AV) from the HSS and the initial UE attach fails.

Which of the following actions is useful for troubleshooting this problem?

```
# cmm nbiPing list --pingTarget 10.10.9.1 --pingSourceIp 10.10.9.2
+-----+-----+-----+-----+-----+-----+-----+-----+
| nbiPing | pingOutput |
+-----+-----+-----+-----+-----+-----+-----+-----+
| 10.10.9.1 | PING 10.10.9.1 (10.10.9.1) from 10.10.9.2 : 56(84) bytes of data.;64 bytes from 10.10.9.1: icmp_seq=1 ttl=64 |
| | time=0.674 ms;64 bytes from 10.10.9.1: icmp_seq=2 ttl=64 time 0.384 ms;64 bytes from 10.10.9.1: icmp_seq=3 ttl=64 |
| | time=0.427 ms;64 bytes from 10.10.9.1: icmp_seq=4 ttl=64 time 0.495 ms;64 bytes from 10.10.9.1: icmp_seq=5 ttl=64 |
| | time=0.426 ms;--- 10.10.9.1 ping statistics ---;5 packets transmitted, 5 received, 0% packet loss, time 4001ms;rtt |
| | min/avg/max/mdev = 0.384/0.481/0.674/0.103 ms; |
+-----+-----+-----+-----+-----+-----+-----+-----+

# cmm multiLink list
+-----+-----+-----+-----+-----+-----+-----+-----+
| multilink | linkInterfaceType | linkIndex | linkAdminState | linkOperationState | alarmState | remoteIp1 | remoteIp2 |
+-----+-----+-----+-----+-----+-----+-----+-----+
| s6ad      | s6ad              | 0         | unlocked       | unknown            | none      | 10.10.9.1 | 0.0.0.0   |
+-----+-----+-----+-----+-----+-----+-----+-----+
```

- A. Verify if the IMSI to HSS mapping list is configured properly.
- B. Verify if a GTP profile is associated with the S6a interface.
- C. Verify if the TAI value matches between the MME and the HSS.
- D. Verify if the DNS server is provisioned to dynamically discover the HSS IP address.

Correct Answer: D

QUESTION 3

Which of the following is NOT performed by the MME during S1-based handover procedure?

- A. MME determines if SGW relocation is required.
- B. MME selects the target eNodeB for handover.

- C. MME releases bearers that are not accepted by the target eNodeB.
- D. MME checks if the handover is to restricted area based on the handover restriction list.

Correct Answer: C

QUESTION 4

Which of the following is NOT an EPS session management (ESM) function performed by MME?

- A. Support default bearer creation, modification, and deletion
- B. Support dedicated bearer creation, modification, and deletion
- C. Inform other network elements about subscription data changes in HSS
- D. Perform network element selection

Correct Answer: A

QUESTION 5

If the selected SGW fails, which SGW/PGW will MME select if `gateway selection mode 2` is used?

- A. A new SGW, but new PGW selection is not required
- B. A new SGW first, then select a new PGW that is topologically closest to the newly selected SGW
- C. A new SGW first, then select a new PGW with the best order and preference values
- D. The next topologically closest SGW/PGW pair

Correct Answer: A

[4A0-M03 Practice Test](#)

[4A0-M03 Study Guide](#)

[4A0-M03 Braindumps](#)