

# 500-920<sup>Q&As</sup>

Cisco Data Center Unified Computing Infrastructure Troubleshooting  
(DCITUC)

## Pass Cisco 500-920 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/500-920.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



#### QUESTION 1

When troubleshooting, which option is the primary uses of the SCOPE command?

- A. To access the log files on the log server
- B. The SCOPE command is not helpful in this case
- C. To access the log files on the virtual machines
- D. To access the log files that reside in a component

Correct Answer: D

---

#### QUESTION 2

Which statement regarding the UCS C-series connectivity modes best describes connectivity options in a UCS Manager integrated environment?

- A. UCS C-series servers must be connected to Fabric Interconnects using Fabric Extenders (FEX)
- B. UCS C-series servers may be connected to multiple UCS Manager domains at the same time
- C. All UCS C-series servers in a single UCS Manager domain must share the same connectivity model
- D. UCS C-series servers may be connected with or without the use of Fabric Extenders (FEX) in environments running UCS Manager Software Release 2.2 or later

Correct Answer: D

---

#### QUESTION 3

A Hard Drive (HDD) has been hot swapped in a UCS server blade, however, the UCS Manager GUI is not displaying updated metrics about the replacement drive. What action will be required to properly display updated metrics?

- A. Remove and re-insert the server blade HDD controller mezzanine card
- B. Reboot the Fabric Interconnects
- C. Reboot the server.
- D. Use the CLI, since HDD metrics cannot be displayed with the UCS Manager GUI

Correct Answer: A

---

#### QUESTION 4

When booting up a Cisco UCS Server you want to see boot time diagnostic messages of the POST, what action is required for you to do so?

- A. Enable Quiet Boot on the Server\\'s BIOS
- B. Restart the Server
- C. Disable Fast Boot on the Server\\'s BIOS
- D. Enable Quiet Boot on the Server\\'s Service Profile
- E. Disable Fast Boot on the Server\\'s Service Profile

Correct Answer: D

---

#### QUESTION 5

When troubleshooting UCS initialization issues that require Fabric Interconnect reboots, which Fabric Interconnect should be rebooted first?

- A. The primary Fabric Interconnect
- B. Both Fabric Interconnects must be rebooted simultaneously
- C. The Cisco UCS Manager will determine with Fabric Interconnect to reboot
- D. The subordinate Fabric Interconnect

Correct Answer: A

[Latest 500-920 Dumps](#)

[500-920 VCE Dumps](#)

[500-920 Practice Test](#)