Pass2Lead
https://Pass2Lead.com

5V0-21.19^{Q&As}

5V0-21.19$^{Q\&As}$

VMware vSAN 6.7 Specialist Exam 2019

Pass VMware 5V0-21.19 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass2lead.com/5v0-21-19.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

What are two reasons why a vCenter UI can show a Noncompliant status for a VM storage object? (Choose two.)

A. The object is no longer fully compliant with the associated storage policy.

B. A storage hardware failure has caused permanent data loss for the object.

C. The VM storage compliance alarm has been triggered for that object.

D. The object is not associated with a guest VM.

E. The object is not associated with a storage policy.

Correct Answer: AE

QUESTION 2

A vSAN administrator has three available racks and six vSAN hosts.

What can a vSAN administrator use to protect against a rack failure while maximizing resources?

A. explicit fault domain

B. vSAN stretched cluster

C. 2-node configuration

D. RAID-6/FTT=2

Correct Answer: A

Reference: https://docs.vmware.com/en/VMware-
vSphere/6.5/com.vmware.vsphere.virtualsan.doc/GUID8491C4B0-6F94-4023-8C7A-FD7B40D0368D.html

QUESTION 3

Which two pre-checks should be taken prior to starting a vSAN upgrade? (Choose two.)

A. disable deduplication/compression

B. upgrade VMware Tools

C. verify vSAN Health

D. upgrade vCenter Server

E. upgrade virtual hardware

Correct Answer: CD

Reference: https://kb.vmware.com/s/article/2146381

QUESTION 4

What is the purpose of slack space in vSAN?

A. Increases overall vSAN capacity

B. Allows for maintenance and failure operations

C. Stores vSphere HA heartbeats

D. Provides vSAN analytic data

Correct Answer: B

Reference: https://storagehub.vmware.com/t/vmware-vsan/vmware-r-vsan-tm-design-and-sizing-guide-2/ how-much-slack-space-should-i-leave-1/

QUESTION 5

The data on a failed disk group is being rebuilt on other disk groups. Negative performance impact to VMs is being reported.

What can be used to reduce the negative performance impact on the VMs?

A. resync throttling

B. maintenance mode

C. proactive rebalance

D. disk group data evacuation

Correct Answer: C

[Latest 5V0-21.19 Dumps](#)   [5V0-21.19 Practice Test](#)   [5V0-21.19 Study Guide](#)