

# 640-911<sup>Q&As</sup>

Introducing Cisco Data Center Networking (Retired)

## Pass Cisco 640-911 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass4lead.com/640-911.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



#### https://www.pass4lead.com/640-911.html 2022 Latest pass4lead 640-911 PDF and VCE dumps Download

#### **QUESTION 1**

What will cause a device to wait a random	amount of time before try	ring to transmit ac	gain?
---	---------------------------	---------------------	-------

- A. signal drop or fade
- B. signal acknowledgment
- C. packet drop
- D. signal collision
- E. keep alive signal
- F. Ethernet silence tone

Correct Answer: D

#### **QUESTION 2**

What option tests hardware to verify that all components of the device are operational and present?

- A. NVRAM
- B. POST
- C. BIOS
- D. Bootstrap

Correct Answer: B

#### **QUESTION 3**

What is the addressing format of IPv6?

- A. 48-bit dotted decimal
- B. 48-bit colon-delimited hexadecimal
- C. 64-bit dotted decimal
- D. 64-bit colon-delimited hexadecimal
- E. 128-bit dotted decimal
- F. 128-bit colon-delimited hexadecimal

Correct Answer: F

"IPv6 addresses are represented as eight groups of four hexadecimal digits separated by colons. The length of an IPv6



#### https://www.pass4lead.com/640-911.html 2022 Latest pass4lead 640-911 PDF and VCE dumps Download

address is 128 bits" http://en.wikipedia.org/ wiki/IPv6

#### **QUESTION 4**

If a Nexus switch receives a frame and does not have an entry in its MAC table for the source, which action will take place?

- A. The frame will be dropped.
- B. The frame will be flooded.
- C. The sender will be notified.
- D. The source address will be learned.

Correct Answer: D

#### **QUESTION 5**

On a new Cisco Nexus switch, you receive an error message when you attempt to create an SVI. What is the first command you must use to create the SVI?

- A. Interface vlan (vlan\_id)
- B. Vlan (vlan\_id)
- C. Feature svi
- D. Interface routed

Correct Answer: A

http://docwiki.cisco.com/wiki/Cisco\_NX-OS/IOS\_Interface\_Comparison ==Configuring a Switched Virtual Interface (SVI)== feature interface-vlan interface vlan 10 ip address 192.168.1.1./24 no shutdown

Latest 640-911 Dumps

640-911 Practice Test

640-911 Exam Questions



To Read the Whole Q&As, please purchase the Complete Version from Our website.

# Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

**Instant Download After Purchase** 

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.pass4lead.com/allproducts

### **Need Help**

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4lead, All Rights Reserved.