

# 642-241<sup>Q&As</sup>

Unified Contact Center Enterprise Design (UCCED)

## Pass Cisco 642-241 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/642-241.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

When a Cisco Unified Contact Center Enterprise agent transfers a call to another agent on a different Cisco Unified Communications Manager cluster, what is the impact if the agent dials the phone number of the second agent directly to perform the transfer?

- A. The second agent will not get screen pop data about the call.
- B. The second agent will not be able to perform a secondary transfer of the call.
- C. The caller will not hear queue music during the transfer.
- D. The different call leg records will be linked in the Cisco Unified Contact Center Enterprise database Termination Call Detail Variable Table.

Correct Answer: A

---

**QUESTION 2**

Which failure scenario in the Cisco Unified Contact Center Enterprise solution would stop all processing and routing of contact center calls?

- A. ICM Call Router Side A fails at the same time that ICM Logger Side A fails.
- B. ICM Call Router Side A fails at the same time that ICM Logger Side B fails.
- C. ICM Call Router Side B fails at the same time that ICM Logger Side A fails.
- D. ICM Call Router Side B fails at the same time that ICM Logger Side B fails.
- E. ICM Call Router Side A fails at the same time that ICM Call Router Side B fails.
- F. ICM Logger Side A fails at the same time that ICM Logger Side B fails.

Correct Answer: E

---

**QUESTION 3**

In the Cisco ICM ConfigManager Peripheral Gateway Explorer, when setting the Peripheral Configuration for the Cisco Unified Communications Manager Multi-Line ACD feature, what are the two expected behaviors of the system when the settings are as shown? (Choose two.)

- A. The CTI Desktop will monitor only one ACD line, but all other lines will be shown on the desktop.
- B. The CTI Desktop will show only the ACD line that the agent used to log in.
- C. If the agent selects another line on the Cisco Unified IP phone, the agent state will change to Not Ready.
- D. If the agent selects another line on the Cisco Unified IP phone, the agent state will not change.

Correct Answer: BD

---

**QUESTION 4**

Cisco provides a VRU Peripheral Gateway to the Central Controller Bandwidth Calculator spreadsheet tool. What is the purpose of this tool?

- A. to size the visible network that is required between the Peripheral Gateway and the call router
- B. to size the private network that is required between the Peripheral Gateway Side A and B
- C. to size the visible network that is required between the Peripheral Gateway and the Cisco Unified Communications Manager cluster
- D. to size the private network that is required between call routers A and B for this specific Peripheral Gateway traffic flow

Correct Answer: A

---

**QUESTION 5**

The Cisco Unified Mobile Agent option for Cisco Unified Contact Center Enterprise supports which of the following modes of operation? (Choose two.)

- A. call-by-call
- B. nailed-up
- C. predictive
- D. preview
- E. progressive

Correct Answer: AB

[Latest 642-241 Dumps](#)

[642-241 Exam Questions](#)

[642-241 Braindumps](#)