

# 642-747<sup>Q&As</sup>

Implementing Cisco Unified Wireless Mobility Services

## Pass Cisco 642-747 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass4lead.com/642-747.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



## https://www.pass4lead.com/642-747.html 2022 Latest pass4lead 642-747 PDF and VCE dumps Download

### **QUESTION 1**

How is the zipped code that is downloaded from Cisco.com handled for a Cisco 3300 Series MSE v7.0 upgrade?

- A. Unzip the file on Cisco WCS before sending to Cisco MSE via TFTP.
- B. Unzip the file on Cisco WCS before sending to Cisco MSE via FTP.
- C. It is automatically unzipped during TFTP from Cisco WCS to Cisco MSE.
- D. It is automatically unzipped during FTP from Cisco WCS to Cisco MSE.

Correct Answer: D

#### **QUESTION 2**

What is the recommendation for the maximum number of APs per VLAN?

- A. 20 to 40
- B. 40 to 60
- C. 60 to 80
- D. 80 to 100
- E. 100 to 120

Correct Answer: C

#### **QUESTION 3**

What are the three conditions that must be met to consider a link between a parent and child to be optimal? (Choose three.)

- A. The link to the parent must offer at least 10-dBm SNR.
- B. Both APs have the same BGN.
- C. The channel to the potential preferred parent can have no interference.
- D. The link to the parent must offer at least 20-dBm SNR.
- E. The channel to the potential preferred parent is not silent or blacklisted.
- F. Both APs must use the default BGN.

Correct Answer: BDE

## https://www.pass4lead.com/642-747.html

2022 Latest pass4lead 642-747 PDF and VCE dumps Download

#### **QUESTION 4**

What is the optimal	distance	between	APs for	location	services?
•					

A. 20 to 40 feet

B. 50 to 70 feet

C. 30 to 50 feet

D. 60 to 80 feet

E. 70 to 90 feet

Correct Answer: B

## **QUESTION 5**

An engineer is maintaining a wireless network with a large amount of RFID tags and notices the WLCs are reporting very high memory utilization. What value should the RFID timeout value be changed to from its default value to alleviate the memory utilization issues?

A. 600

B. 1200

C. 7200

D. 14400

Correct Answer: A

642-747 Practice Test

642-747 Study Guide

642-747 Exam Questions



To Read the Whole Q&As, please purchase the Complete Version from Our website.

## Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

**Instant Download After Purchase** 

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.pass4lead.com/allproducts

## **Need Help**

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4lead, All Rights Reserved.