



642-998^{Q&As}

Designing Cisco Data Center Unified Computing

Pass Cisco 642-998 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4lead.com/642-998.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Which two devices require a connection to an external switch for East-West switching? (Choose two.)

- A. Cisco Nexus 3548
- B. Cisco UCS 6248UP
- C. Cisco UCS 2208XP
- D. Cisco Nexus 2232PP
- E. Cisco UCS 6296UP

Correct Answer: CD

QUESTION 2

Your Cisco UCS design contains this hardware:

2 x 6248UP Fabric Interconnects

1 x 5108 Chassis containing a pair of 2204XP IO Modules

8 x B200M3 blades, each with a VIC 1240 and no mezzanine adapter

What is the maximum available bandwidth per fabric for each server?

- A. 10 Gb
- B. 20 Gb
- C. 40 Gb
- D. 80 Gb
- E. 160 Gb

Correct Answer: A

QUESTION 3

Which two characteristics are associated with the core layer of a Cisco Data Center Unified Fabric network? (Choose two.)

- A. no packet manipulation
- B. QoS ?policing



- C. voice, data, and wireless convergence
- D. scalable routing protocols
- E. provides default gateway redundancy
- F. QoS ?classification and queuing

Correct Answer: AD

QUESTION 4

Which protocol is best suited for connecting two data centers together?

- A. LISP
- B. OTV
- C. FabricPath
- D. vPC

Correct Answer: B

QUESTION 5

You are designing a Cisco UCS Solution that uses Cisco VIC 1280 Mezzanine Adapters. Which design decision helps prevent potential bottlenecks in the system?

- A. Configure a NIC team, and use per VM load balancing in vCenter.
- B. Use the VIC 1280 in combination with the 2208XP IO Module.
- C. Ensure all links between the Cisco Fabric Interconnect and IO Module are configured as a port channel.
- D. Utilize all links between the Cisco Fabric Interconnect and IO Module.
- E. Configure the vNIC for an MTU of 9000.

Correct Answer: C

[642-998 VCE Dumps](#)

[642-998 Study Guide](#)

[642-998 Exam Questions](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.pass4lead.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4lead, All Rights Reserved.