

9L0-012^{Q&As}

Mac Service Certification Exam

Pass Apple 9L0-012 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/9L0-012.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Apple
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which of the following tools is a quick system-level diagnostic test used to verify module presence and sensor readings?

- A. Apple Service Diagnostic (ASD)
- B. Notebook Adapter Diagnostic (NAD)
- C. Mac Resource Inspector (MRI)
- D. Cooling System Diagnostic (CSD)

Correct Answer: A

Reference: http://tim.id.au/laptops/apple/macbook/mbp15_mid2010.pdf (page 18)

QUESTION 2

How often should the ESD mat be cleaned?

- A. Once a year
- B. Once a week
- C. Once a month
- D. Every few years

Correct Answer: C

QUESTION 3

Which component for Apple Service Toolkit is designed to help troubleshoot issues with MagSafe and MagSafe 2 power adapters?

- A. NAD
- B. VST
- C. TPT
- D. CSD

Correct Answer: A

Explanation:

Apple Service Toolkit includes:*

AudioTest — plays a series of tones through each speaker and listens for those same tones via the microphone.

Diagnostic Gateway (DG) — software that runs on a dedicated Intel-based Mac using Mac OS X Server 10.6/10.7 and serves up tools to triage computers via NetBoot, recording test results as log files.

Mac Resource Inspector (MRI) — triage tool that provides a fast check of internal hardware components for all Intel- based computer systems.

Notebook Adapter Diagnostic (NAD) — triage tool that reports on the condition of Intel-based notebook power adapters.

Cooling System Diagnostic (CSD) – evaluates the thermal sensors, fans and heat sink in MacBook Pro (Early 2011) models and will either confirm correct operation or help diagnose a service issue.

Gateway Manager — software application used to remotely configure and manage the Diagnostic Gateway server as well as access logs created by diagnostic tools.

Test Patterns Tool (TPT) – identifies pixel anomalies in LCD panels in Apple Display, iMac, MacBook, MacBook Pro, and MacBook Air systems.

Server Bit Setter (SBS) – Repair tool used after replacing logic boards in late model Mac mini Servers or backplane boards in late model Mac Pro Servers.

Video System Test (VST) – is used to test video issues in specific MacBook Pro models.

Blank Board Serializer (BBS) – Allows technicians to set the system serial number on replacement Main Logic Board (MLB) service parts.

AST Keyboard (OS) – service tool for in-depth testing of keyboards.

AST Trackpad (OS) – service tool for in-depth testing of trackpads.

Storage Diagnostic (OS) – Repair tool for testing HDD or SSD modules.

Image Persistence Test (EFI) – triage tool for identifying image persistence anomalies on IPS displays

QUESTION 4

If an issue is in the Hardware problem space, which of the following should be removed from the Apple product to further isolate the issue?

- A. All third party equipment
- B. Any third party applications
- C. Any third party extensions
- D. Any third party frameworks

Correct Answer: A

QUESTION 5

When conducting an internal inspection of MacBook Air (13-inch, Mid 2011) for accidental damage, why is it necessary to remove the battery?

- A. There are liquid contact indicators on the underside of the battery module.
- B. The battery is always removed in every repair on this unit.
- C. The battery covers all of the spill sensors on the top case.
- D. The battery must be removed to install the battery cover.

Correct Answer: A

Reference: <http://www.mybigcampus.com/bundles/unit-5-accidental-damage-and-macbook-air--- 276227>

[9L0-012 PDF Dumps](#)

[9L0-012 VCE Dumps](#)

[9L0-012 Braindumps](#)