

# E20-326<sup>Q&As</sup>

Symmetrix Solutions Design Exam for Technology Architects Exam

## Pass EMC E20-326 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/e20-326.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Which encoding scheme is used by 10 Gb/s fibre channel transmission?

- A. 64b/66b
- B. 8b/10b
- C. 16b/18b
- D. 32b/34b

Correct Answer: A

---

**QUESTION 2**

A customer plans to aggregate a number of CLARiiONs to a Symmetrix VMAX with FAST VP. Which data collection requirements are recommended for a Tier Advisor analysis?

- A. Minimum 5 hour NAR and trace data collection with both NAR and trace data collected at 2 minute intervals.
- B. Trace data for 30 minutes each hour of NAR capture. Minimum 8 hour NAR data collection at 10 minute intervals for coarse data analysis.
- C. Trace data at 1 minute intervals for detailed peak data capture. Maximum 24 hour NAR and trace capture at default 10 minute intervals to enable peak analysis on a daily basis.
- D. Minimum 5 day NAR with default data collection interval of 10 minutes. Partial trace data for 30 minutes each hour of NAR capture.

Correct Answer: A

---

**QUESTION 3**

A customer needs to configure SRDF/S between two sites 10 km apart. The customer connected the R1 ports to fabric-A at site 1 and the R2 ports to fabric-B at site 2. The customer does not want to merge the two fabrics between sites.

What is the recommended solution?

- A. Implement FC routing or Virtual SAN to isolate the fabric
- B. Implement FCIP connection to isolate the fabric
- C. Merge two fabrics, and zone R1 and R2 ports.
- D. Connect the RDF ports using DWDM or SONET.

Correct Answer: A

---

**QUESTION 4**

A customer has a pair of VMAX arrays configured to replicate thin devices at one site to thin devices at another site using SRDF/A. The customer wants to implement TimeFinder/Snap replication of the R2 device on the target array and asks you to confirm this is a supported configuration. What do you advise the customer?

- A. No, it is not supported.
- B. It is supported only if the precopy option is used.
- C. Yes, it is supported.
- D. It is supported only if composite groups are used.

Correct Answer: B

---

**QUESTION 5**

Which host-based performance tool should be used to gather data for Microsoft Windows systems?

- A. PERFMON
- B. SAR
- C. IOSTAT
- D. NAR

Correct Answer: A

[Latest E20-326 Dumps](#)

[E20-326 Study Guide](#)

[E20-326 Exam Questions](#)