

E20-326^{Q&As}

Symmetrix Solutions Design Exam for Technology Architects Exam

Pass EMC E20-326 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/e20-326.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

An SRDF/S implementation is being designed. The RA performance limits are 3800 4k IOPS for a Fibre RF adapter. The application is doing 6000 4k IOPS with 30% writes and uses multiple volumes. How many RAs are recommended?

- A. 2
- B. 1
- C. 4
- D. 6

Correct Answer: A

QUESTION 2

You are designing the Symmetrix VMAX architecture for a DAS-to-SAN SQL Server migration. Currently all user databases reside on a single locally-attached disk enclosure, mounted to "M:". You have decided on RAID-1 protected 15,000 RPM drives for the new SQL environment.

Day 1		Day 2		Day 3		Day 4		Day 5	
Read	Write	Read	Write	Read	Write	Read	Write	Read	Write
858	1036	1067	903	1010	921	877	1078	841	855
1082	958	971	961	1047	1159	899	892	1080	956
829	1022	904	884	786	998	1191	917	1132	1146
780	1032	1123	879	877	1022	944	1130	981	1088
1165	1167	1079	1026	786	988	781	1076	841	1052
825	1113	758	1080	898	1140	984	1196	954	880
1152	994	894	921	817	1060	1036	980	930	994
1001	1175	762	1133	971	1200	1091	907	1045	997

Last week, you configured Perfmon to record the current IOPS load as shown in the exhibit. Following EMC best practices, what is the minimum number of spindles required to satisfy the performance needs of the database?

- A. 9
- B. 10
- C. 18
- D. 20

Correct Answer: C

QUESTION 3

What is the Write Load Adjustment Factor recommended by Performance Engineering when modeling an SRDF/A

solution with BCSD?

- A. 1.5
- B. 2
- C. 3
- D. None

Correct Answer: A

QUESTION 4

Which condition results in effective prioritization by Symmetrix Priority Controls (SPC)?

- A. Application classes are isolated on different disks/tiers.
- B. Different application classes share the same physical disks.
- C. Applications share the same physical disks and have different IO profiles.
- D. Applications share the same physical disks and are active at different times,

Correct Answer: B

QUESTION 5

What is the size of a fibre channel frame?

- A. 2112 bytes
- B. 1500 bytes
- C. 9000 bytes
- D. 2148 bytes

Correct Answer: D

[E20-326 VCE Dumps](#)

[E20-326 Practice Test](#)

[E20-326 Study Guide](#)