

E20-616^{Q&As}

Symmetrix Installation and Troubleshooting Specialist

Pass EMC E20-616 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/e20-616.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

You are asked to add SRDF to a VMAX 20K that is currently at 5876. After you install Enginuity 5876 on your desktop, how should you upgrade the IMPL.BIN?

- A. Login as ENG, select Access level expert
- B. Login as CE, select Access level expert
- C. Login as Configuration group, select Access level standard
- D. Login as Configuration group, select Access level expert

Correct Answer: A

QUESTION 2

What is a characteristic of VMAX 40K Power Vault Hypers (PVDs)?

- A. PVDs are 9 GB in size.
- B. There are two PVDs per physical disk drive.
- C. Space is allocated for PVDs in Global Memory.
- D. PVDs are 5 GB in size.

Correct Answer: A

QUESTION 3

What is the Best Practice when configuring Fast VP volumes?

- A. Data devices should have the same emulation.
- B. Data devices should have different protection type.
- C. Data device in a pool can be of different rotational speed.
- D. Data devices in a pool can be different in size.

Correct Answer: A

QUESTION 4

What is the EMC recommended best practice when configuring a volume on a VMAX 10K?

- A. Configured as a THIN device

- B. Configured as a THICK device
- C. Configured as an SRDF device
- D. Configured as a DSE device

Correct Answer: A

QUESTION 5

What is the power level required for VMAX 20K Standard Storage Bay?

- A. 5.3 kVA
- B. 2.5 kVA
- C. 4.9 kVA
- D. 3.5 kVA

Correct Answer: A

[Latest E20-616 Dumps](#)

[E20-616 Study Guide](#)

[E20-616 Braindumps](#)