

HC-711-ENU^{Q&As}

HCNA Huawei Certified Network Associate - Constructing Basic Security Network (HCNA-CBSN) - ENU

Pass Huawei HC-711-ENU Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hc-711-enu.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

SVN support the following types of file-sharing, which has several? (Choose two)

- A. SMB
- B. Windows
- C. NFS
- D. Linux

Correct Answer: AC

QUESTION 2

L2TP VPN, and L2TP tunnels and sessions on the statement is correct: (Choose two)

- A. Between the same pair of LAC and LNS can create multiple L2TP tunnel,the tunnel consists of a control connection and at least one session (Session) composition
- B. Tunnel multiplexed on the session connection for the session,said carrying PPP tunnel connecting each
- C. After the session connection must be established successfully in the tunnel
- D. L2TP tunnel control message transmission, data message transmission in the session

Correct Answer: AC

QUESTION 3

IPSEC WEB configuration wizard which does not support the following scenarios?

- A. Gateway to Gateway
- B. Gateway Center
- C. Branch Gateway D. Host and Host

Correct Answer: D

QUESTION 4

IPSec by AH (Authentication Header) and ESP (Encapsulating Security Payload) protocol to achieve these two private security, integrity, authenticity, and anti-replay, and also through IKE (Internet Key Exchange) provides auto-negotiation exchanged for IPSec key to establish and maintain security alliance services to simplify the use and management of IPSec.

- A. True

B. False

Correct Answer: A

QUESTION 5

When configuring I2tp, for commands allow I2tp virtual-template, statements is correct?

- A. LNS is used to specify the trigger condition to initiate a call
- B. LAC is used to specify the trigger condition to initiate a call
- C. LAC is used to specify the call to accept Virtual-Template used
- D. LNS to accept the call to specify the use of Virtual-Template

Correct Answer: D

[Latest HC-711-ENU Dumps](#) [HC-711-ENU PDF Dumps](#) [HC-711-ENU Study Guide](#)