

HH0-210^{Q&As}

HDS Certified Implmenter-Enterprise

Pass Hitachi HH0-210 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hh0-210.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

What is the maximum number of 3.5" HDDs per B4 unit in a VSP?

- A. 32
- B. 40
- C. 60
- D. 64

Correct Answer: B

QUESTION 2

Which step must be performed when preparing for Hitachi Dynamic Provisioning operations?

- A. Create Pool Vol LDEVs.
- B. Map Pool Vol LDEVs to FED ports.
- C. Cross-link the mapping tables.
- D. Create a CLPR for pool LDEVs.

Correct Answer: A

QUESTION 3

You arrive on site to work on a VSP system and observe that the front panel "Message" LED is on. What does this indicate?

- A. HiTrack is not configured.
- B. The SVP is in Modify mode.
- C. A SIM is pending.
- D. Remote maintenance is being performed on the system.

Correct Answer: C

QUESTION 4

You have just installed Hitachi Dynamic Link Manager (HDLM) on a Sun Solaris server. What is the purpose of running the "dlnkmgr view -sys" command?

- A. It displays the configuration.
- B. It displays the primary path.
- C. It displays the alternate path.
- D. It configures the alternate path.

Correct Answer: A

QUESTION 5

What is Hitachi Data System's recommended practice for zoning?

- A. port-based zoning
- B. zoning is optional
- C. single HBA zoning -- one HBA per zone
- D. single operation system zoning -- all HBAs from one OS in a zone

Correct Answer: C

[HH0-210 VCE Dumps](#)

[HH0-210 Study Guide](#)

[HH0-210 Braindumps](#)