

HH0-220^{Q&As}

HDS Certified Implmenter-Modular

Pass Hitachi HH0-220 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hh0-220.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

After the removal of a failed disk drive on a Hitachi Unified Storage system, how long should you wait before inserting a new drive?

- A. no need to wait
- B. more than 5 seconds
- C. more than 10 seconds
- D. more than 20 seconds

Correct Answer: D

QUESTION 2

What are two ways to restrict access to storage through a Fabric? (Choose two.)

- A. Use SNMP
- B. Use zoning
- C. Use Host Group security
- D. Useport security on the switch(es)

Correct Answer: BC

QUESTION 3

An administrator wants to install Hitachi Dynamic Link Manager (HDLM) on a Solaris server. Which two are required before performing the installation? (Choose two.)

- A. The server must have IPv6 disabled.
- B. A valid HDLM license must be obtained.
- C. The server must be in a dual path configuration.
- D. The processes of all applications accessing the devices to be managed by HDLM must be terminated.

Correct Answer: BD

QUESTION 4

You have set Extended Round Robin on a server with intensive sequential I/O profile. Which two benefits result from implementing this algorithm? (Choose two.)

- A. tracks preloaded to cache
- B. blocks held permanent in Read Cache
- C. no tracks preloading on the system
- D. efficient cache usage on the storage system

Correct Answer: AD

QUESTION 5

What are three characteristics of the Hitachi Unified Storage systems active/active controller design? (Choose three.)

- A. SNM2 GUI is used to turn on active/active controller processing.
- B. Workload is automatically balanced between controllers.
- C. When creating a LUN the default controller must be selected.
- D. The processor of Ctrl0 can access the Fibre Channel (FC) ports of Ctrl1.
- E. Non disruptive firmware upgrade is possible even if a host is connected by only one path.

Correct Answer: BDE

[Latest HH0-220 Dumps](#)

[HH0-220 PDF Dumps](#)

[HH0-220 Exam Questions](#)