

# HH0-450<sup>Q&As</sup>

Hitachi Data Systems Storage Architect-Hitachi NAS Platform

## Pass Hitachi HH0-450 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hh0-450.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

A customer requires an asynchronous replication solution for their Hitachi NAS Platform. They have two data centers that are over 500 km apart. They are concerned with intermittent network connectivity problems and would like to leverage disk-based journaling. Which block-based replication should be used?

- A. ShadowImage
- B. TrueCopy
- C. Universal Replicator
- D. TrueCopy Asynchronous

Correct Answer: C

---

**QUESTION 2**

A customer has 28 independent file servers with various amounts of data on each server and they would like to consolidate with a Hitachi NAS Platform. Which three factors must be considered prior to the consolidation? (Choose three.)

- A. number of concurrent users
- B. type of applications and specific purpose of each application server
- C. server BIOS version
- D. number of mount points and shares
- E. number of concurrent HTTP instances

Correct Answer: ABD

---

**QUESTION 3**

You are creating a deployment plan for a new Hitachi NAS Platform customer that will meet their recovery and data consolidation requirements for their NFS and CIFS data. Which two key infrastructure areas must you identify for the design? (Choose two.)

- A. Recovery Point Objective
- B. types of servers
- C. Recovery Time Objective
- D. number of NDS servers

Correct Answer: AC

---

**QUESTION 4**

Your customer wants to issue administrative commands to a Hitachi NAS Platform over their data network using scripting. The clients on the data network have no routes defined to allow access on the management network. What must you do?

- A. Change the firewall setting in SMU to allow access to the admin EVS.
- B. Assign an IP address to the admin EVS on the data network aggregate.
- C. Run the scripted commands against any existing file services EVS.
- D. Add an additional IP address to the file services EVS used by the clients.

Correct Answer: B

---

**QUESTION 5**

When configuring iSCSI initiators, which two must be configured to facilitate dynamic target (server) discovery from the Hitachi NAS platform? (Choose two.)

- A. the iSCSI LUN
- B. the iSCSI target portal
- C. the iSCSI IQN
- D. the iSNS

Correct Answer: BD

[Latest HH0-450 Dumps](#)

[HH0-450 PDF Dumps](#)

[HH0-450 VCE Dumps](#)