

# HP0-J63<sup>Q&As</sup>

Designing HP Backup Solutions

**Pass HP HP0-J63 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hp0-j63.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

A company needs to identify the WAN link requirements to replicate D2D systems across sites. Which tool does HP recommend to accomplish this task?

- A. HP Storage Sizing Tool
- B. HP Systems Insight Manager
- C. DNS Connection Check
- D. Data Storage Product Configurator

Correct Answer: A

---

**QUESTION 2**

Which type of deduplication uses hash-based chunking technology?

- A. switch-based
- B. post processing
- C. inline
- D. virtual

Correct Answer: C

<http://bizsupport2.austin.hp.com/bc/docs/support/SupportManual/c02511912/c02511912.pdf>

---

**QUESTION 3**

What should the customer use for critical data?

- A. data deduplication
- B. remote replication
- C. snapclones
- D. snapshots

Correct Answer: B

---

**QUESTION 4**

A company uses an HP Enterprise Backup Solution with an HP StoreSure 2000 and a shared tape library for backups to a remote location. In which directions will data flow between devices during a backup job? (Select two)

- A. from the storage system to a replication site
- B. from a host to the storage system
- C. from a host to a replication site
- D. from the storage system to the tape library
- E. from the storage system to a host
- F. from a host to the tape library

Correct Answer: EF

---

#### QUESTION 5

A storage administrator is running SAN monitoring software on a server other than the backup server. The software is interfering with scheduled backups in the company's tape library. Which action should the administrator take to minimize interference with the operation of the tape devices?

- A. Install the minimum patch-level support for the monitoring software.
- B. Enable the use of SCSI reserve and release.
- C. Modify the kernel tunable parameter vx\_ninode.
- D. Implement single initiator zoning.

Correct Answer: D

Enable the use of SCSI reserve and release is for protection error human with tape, not interfering schedule backups with SAN monitoring SCSI reserve or release A device-level protection that is used by Enterprise Media Manager (EMM) to avoid unintended sharing of tape devices and possible data loss problems.

[http://www.symantec.com/security\\_response/glossary/define.jsp?letter=s&word=scsi-reserve-or-release](http://www.symantec.com/security_response/glossary/define.jsp?letter=s&word=scsi-reserve-or-release)

[HP0-J63 VCE Dumps](#)

[HP0-J63 Study Guide](#)

[HP0-J63 Braindumps](#)