

HP0-J65^{Q&As}

Designing HP SAN Networking Solutions

Pass HP HP0-J65 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hp0-j65.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A company is running an application that is READ intensive. They are more concerned with effective READ performance than WRITE performance. They have a limited number of disks so they need to minimize RAID overhead. What type of RAID should they use?

- A. RAID 5
- B. RAID 1+0
- C. RAID 1
- D. RAID 0

Correct Answer: A

QUESTION 2

Which type of HP Devices would be appropriate for the network displayed in the exhibit? Select three.

- A. MPX100
- B. MPR400
- C. MPR600
- D. MDS9220i
- E. MPX110
- F. MDS9222i

Correct Answer: BEF

QUESTION 3

What is the biggest challenge for a SAN environment designer?

- A. designing a solution to solve the business problem
- B. deciding which SAN topology is easiest to implement
- C. selecting the switch vendor who offers the fastest products
- D. sizing the storage system to meet the current requirements

Correct Answer: A

QUESTION 4

A large customer has a SAN infrastructure with six HP 8/40 SAN switches in each redundant fabric. To accommodate growing workload and expected growth on the SAN, the customer wants to replace their switches. They also want to reduce associated costs for power, cooling, and management. The IT Director wants additional capabilities for monitoring and alerting in the new environment.

Which SAN infrastructure solution should you recommend in your proposal?

- A. HP SN8000C Director with Cisco Fabric Manager Server
- B. HP SN8000B 8-Slot Power Pack + SAN Director
- C. HP SN8000B 8-Slot SAN Director
- D. HP SN8000B 4-Slot Power Pack + SAN Director

Correct Answer: A

QUESTION 5

Which fabric rule is valid?

- A. In a C-Series fabric, the default access is Allow All
- B. Routing must be configured manually if switches from different vendors are present in the same fabric
- C. Dynamic Load Sharing (DLS) must be set to the default setting of ON for non-Continuous Access configuration
- D. If HP-UX hosts are in the fabric, the principal switch should have a Domain ID of 8

Correct Answer: C

[Latest HP0-J65 Dumps](#)

[HP0-J65 Practice Test](#)

[HP0-J65 Exam Questions](#)