

# JN0-343<sup>Q&As</sup>

Juniper Networks Certified Internet Specialist (JNCIS-ENT)

## Pass Juniper JN0-343 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/jn0-343.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

-- Exhibit -

```
user@R1> show route 66.129.0.0/22 exact detail

inet.0: 12 destinations, 12 routes (11 active, 0 holddown, 1 hidden)

66.129.0.0/22 (1 entry, 1 announced)

*Aggregate Preference. 130

Next hop type. Reject

Next-hop reference count: 2

State.

Age. 1:39:21

Task: Aggregate

Announcement bits (1): 0-KRT

AS path: I (LocalAgg)

Flags: Depth: 0 Active

AS path list:

AS path: I Refcount: 3

Contributing Routes (3):

66.129.0.0/24 proto Direct

66.129.1.0/24 proto Direct

66.129.2.0/24 proto Direct
```

-- Exhibit -

In the exhibit, R1 receives a packet with a destination address of 66.129.3.1.

Which action does R1 take on the packet?

- A. R1 rejects the packet and sends an unreachable message back to the source.
- B. R1 forwards the packet to the next hop associated with the primary contributing route.
- C. R1 forwards the packet to the next hop associated with the contributor with the lowest RID.
- D. R1 silently discards the packet.

Correct Answer: A

### QUESTION 2

A switch has just come online and currently has no learned unicast entries in its bridge table. Which two statements regarding this switch and its operations are true? (Choose two.)

- A. All frames received through a switch port will be flooded out all other switch ports belonging to the same VLAN.
- B. All broadcast frames received through a switch port will be flooded out all switch ports, regardless of the VLAN.
- C. The switch will dynamically add MAC entries to the bridge table for the destination MAC address listed in received frames.
- D. The switch will dynamically add MAC entries to the bridge table for the source MAC address listed in received frames.

Correct Answer: AD

---

### QUESTION 3

Which two statements are correct about how EX Series switches support STP and RSTP interoperability? (Choose two.)

- A. A switch running only STP accepts RSTP BPDUs and discards the RSTP-specific information.
- B. A switch running only STP discards RSTP BPDUs.
- C. A switch running RSTP accepts STP BPDUs and responds using STP BPDUs.
- D. A switch running RSTP accepts STP BPDUs and responds using RSTP BPDUs.

Correct Answer: BC

---

### QUESTION 4

Which three attributes are considered in the default configuration of per-flow load balancing for routed IPv4 traffic? (Choose three.)

- A. incoming interface
- B. source MAC address
- C. protocol
- D. source IP address
- E. destination port

Correct Answer: ACD

---

**QUESTION 5**

You want to configure filter-based forwarding. What are the three required configuration elements? (Choose three.)

- A. routing instance
- B. firewall filter
- C. policy statement
- D. prefix list
- E. RIB group

Correct Answer: ABE

[Latest JN0-343 Dumps](#)

[JN0-343 PDF Dumps](#)

[JN0-343 Study Guide](#)