

NS0-163^{Q&As}

Network Appliance Data Protection Solutions

Pass NetApp NS0-163 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/ns0-163.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

You are troubleshooting a clustered failover problem at a customer site. The customer explains that both storage appliances were NFS mounted onto the Solaris host. You attempt to create a file on the NFS mount point for the inaccessible appliance, but you get the following error:NFS server filer2 not responding still trying.Symptoms:

- 1) When not in takeover mode, both storage appliances operate normally.
- 2) In takeover mode, the taken over node is not accessible on the network.You perform a "cf giveback" and you can now create a file over NFS on both appliances.

What should you do first to resolve this issue?

- A. Replace the cluster interconnect card and run diagnostics "all" to ensure proper system operation.
- B. Replace the NIC adapter.
- C. Use the cluster-config-checker.cgi to identify the problem and corrective action.
- D. Submit a new bug report.

Correct Answer: C

QUESTION 2

A volume can contain up to___snapshots concurrently.

- A. 125
- B. 225
- C. 255
- D. Depends on capacity and number of disk drives

Correct Answer: C

QUESTION 3

Which three of the following configurations would increase data transfer rates for traditional volume SnapMirror?

- A. The destination and source contain disks of the same size.
- B. The destination and source contain RAID groups of the same size.
- C. The destination and source storage appliances are no further than 30 meters apart.
- D. The destination and source contain the same number of RAID groups.

Correct Answer: ABD

QUESTION 4

In cluster takeover mode, the shared interface assumes the identity of the:

- A. local interface only
- B. failed partner interface only
- C. local and failed partner interfaces
- D. None of the above

Correct Answer: C

QUESTION 5

The required hardware to add SyncMirror to an existing system would be _____.

- A. disk shelves and cluster interconnect
- B. disk shelves and termination switches
- C. disk shelves, Ethernet adapters, and cabling
- D. disk shelves, Fibre Channel adapters, and cabling

Correct Answer: D

[NS0-163 PDF Dumps](#)

[NS0-163 Practice Test](#)

[NS0-163 Braindumps](#)