

NS0-502^{Q&As}

NetApp Certified Implementation Engineer-SAN and Virtualization

Pass NetApp NS0-502 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass2lead.com/ns0-502.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

Which option needs to be set on a LUN to guarantee that it cannot be affected by other LUNs in the volume?

- A. Volume Guarantee
- B. Volume Space Reserved
- C. LUN Reservation Disabled
- D. LUN Reservation Enabled

Correct Answer: D

QUESTION 2

A company has five Windows servers that are dual-attached, four Linux servers that are single- attached, and ten dualattached Solaris servers. The company wants a highly available architecture. A dual controller FAS3100 series with all onboard FC ports connected to the fabric is being proposed.

What is the total number of FC ports and what type of fabric should be deployed from the choices shown?

- A. single fabric with 38 ports total
- B. dual fabrics with 38 ports total
- C. dual fabrics with 42 ports total
- D. single fabric with 42 ports total

Correct Answer: C

QUESTION 3

You are creating an acceptance test plan and the subject of performance is raised.

How should you define what the minimum performance should be?

- A. You should look up the test results for a similar system in previous performance testing and use those numbers.
- B. You should work with the customer to understand their performance expectations and determine the minimum performance they require for the application this system will support.
- C. You should use the published maximum performance specifications for this system.
- D. You should use the published minimum performance specifications for this system.

Correct Answer: B

https://www.pass2lead.com/ns0-502.html

QUESTION 4

Which utility on Solaris 10 can be used to collect information about firmware and driver versions for a Qlogic QLAxxx/QLExxxx HBA?

- A. EMutil
- B. SANutil
- C. cfgadmin
- D. SANsurfer
- E. HBAnywhere

Correct Answer: D

QUESTION 5

Zoning by World Wide Port Name (WWPN) is deployed and a host HBA is replaced. Which zone change needs to be made?

- A. No changes are necessary.
- B. The zone configuration should be changed to include the port to which the HBA is connected.
- C. The zone configuration should be changed to include the WWPN of the new HBA; the old WWPN will be automatically dropped.
- D. The zone configuration should be changed to include the WWPN of the new HBA and to remove the WWPN of the old HBA.

Correct Answer: D

Latest NS0-502 Dumps

NS0-502 VCE Dumps

NS0-502 Practice Test