

C9530-410^{Q&As}

IBM MQ V8.0 System Administration

Pass IBM C9530-410 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/c9530-410.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

A system administrator has migrated a z/OS queue manager from a previous version to V8.0.0. Which action does the system administrator need to take to implement the larger 8-byte Relative ByteAddressRBAfortheactivelogs?

- A. Deleteandrede netheactivelogs.
- B. Run CSQJUFMT to format the active logs to use the larger RBA.
- C. Start the queue manager. The RBA size is automatically updated at migration time.
- D. EnablenewfunctionmoderunCQSJUCNVtoconverttheBootstrapDataSetBSDS.

Correct Answer: C

QUESTION 2

IBM MQ for z/OS recovery routines experienced an issue which resulted in an X\\'5C6" abend. What type of dump needs to be investigated by the system administrator if no dump location has been speci ed by JCL?

- A. SVC
- B. Snap
- C. Stand-alone
- D. SYSUDUMP

Correct Answer: A

QUESTION 3

On a Linux system, a system administrator needs to change the default queue manager from QM1 to a newly created queue manager QM2.

How can the system administrator do this?

- A. Re-createQM2withthe-dooption.
- B. Use the ALTER QMGR command.
- C. Edit the DefaultQueueManager stanza in qm.ini replacing QM1 with QM2.
- D. Change the queue manager name on the Name a ribute of the DefaultQueueManager stanza to QM2 in mqs.ini.

Correct Answer: D

QUESTION 4

A system administrator of a z/OS queue manager expects to have 1000 client channels connecting with the queue manager at the same time.

What should system administrator do to tune the channel initiator to handle this work?

- A. Use the default values for the channel initiator parameters.
- B. Increase MAXCHL, ACTCHL, TCPCHL, CHIADAPS, and CHIDISPS from the default values.
- C. Increase CHIADAPS and use the default values for CHIDISPS, MAXCHL, ACTCHL, TCPCHL.
- D. Increase CHIADAPS and CHIDISPS and use the default values for MAXCHL, ACTCHL, TCPCHL.

Correct Answer: B

QUESTION 5

A new local queue named ACCOUNTQ has been created on queue manager QMA to be used by a client application. The application user is \\appusr\\ who will be required to browse and destructively read messages, and to query queue attributes. The MQ server runs on an AIX host. Which command does a system administrator need to run?

- A. setmqaut -m QMA -t queue -n ACCOUNTQ -p appusr +get +browse +inq
- B. setmqaut -m QMA -t queue -n ACCOUNTQ -p appusr +inq +browse +set
- C. setmqaut -m QMA -t queue -n ACCOUNTQ -p appusr +browse +get +setid
- D. setmqaut -m QMA -t queue -n ACCOUNTQ -p appusr +connect +get +browse +set

Correct Answer: B

[Latest C9530-410 Dumps](#)

[C9530-410 Practice Test](#)

[C9530-410 Study Guide](#)