

# CWNA-106<sup>Q&As</sup>

Certified Wireless Network Administrator

**Pass CWNP CWNA-106 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/cwna-106.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



### QUESTION 1

What advantages does using predictive site survey modeling software offer over performing a manual site survey? (Choose 2)

- A. Predictive modeling software can predict the ideal access point location 100% of the time, whereas the results from manual surveying are less reliable.
- B. Predictive modeling software makes it simple to assess multiple different AP locations and then adjust and display the AP's expected coverage pattern in almost real-time.
- C. Predictive modeling software provides more reliable data than manual surveys when fine-tuning and validating access point placement after the installation.
- D. The exact impact of interference sources from external networks can be more accurately measured when using predictive modeling software than with manual surveys.
- E. It takes less time to create an initial site survey for a large facility when using predictive modeling software than when performing a manual survey.

Correct Answer: BE

---

### QUESTION 2

To ease user complexity, your company has implemented a single SSID for all employees. However, the network administrator needs a way to control the network resources that can be accessed by each employee based on their department. What WLAN feature would allow the network administrator to accomplish this task?

- A. SNMP
- B. VRRP
- C. RBAC
- D. IPSec
- E. WIPS
- F. WPA2

Correct Answer: C

---

### QUESTION 3

What features were introduced in the IEEE 802.11h amendment in order to uphold regulatory requirements for 5 GHz operation? (Choose 2)

- A. 256-QAM
- B. Distributed Coordination Function (DCF)

- C. Phase Shift Keying (PSK)
- D. Transmit Power Control (TPC)
- E. Radio Resource Management (RRM)
- F. Dynamic Frequency Selection (DFS)

Correct Answer: DF

---

#### QUESTION 4

What causes of hidden nodes within a BSS would be more likely lead to an increase in collisions and retries? (Choose 2)

- A. Data frames too large for the physical environment
- B. Client stations broadcasting with too much power
- C. Access points broadcasting with too little power
- D. Client stations too close in proximity to each other
- E. Obstacles between client stations causing attenuation
- F. Large 802.11 cells with physically distributed stations

Correct Answer: EF

---

#### QUESTION 5

What statement describes the authorization component of a AAA implementation?

- A. Verifying that a user is who he says he is
- B. Validating client device credentials against a database
- C. Logging the details of user network behavior in order to review it at a later time
- D. Granting access to specific network services according to a user profile
- E. Implementing a WIPS as a full-time monitoring solution to enforce policies

Correct Answer: D

[Latest CWNA-106 Dumps](#)

[CWNA-106 Study Guide](#)

[CWNA-106 Exam Questions](#)